View NSN Online: https://aerobasegroup.com/nsn/8030-01-177-5620

DOW CORNING (CORP HQ) -- 3-6548 SILICONE RTV FOAM, PART A -- 8030-01-177-5620

======== Product Identification ============

Product ID:3-6548 SILICONE RTV FOAM, PART A

MSDS Date:10/24/1991

FSC:8030

NIIN:01-177-5620

Kit Part:Y

MSDS Number: BBZNV === Responsible Party ===

Company Name: DOW CORNING (CORP HQ) Address: 2200 WEST SALZBURG ROAD

Box:997

City:MIDLAND

State:MI ZIP:48686 Country:US

Info Phone Num:800-24

8-2481 PROD INFORMATION

Emergency Phone Num:517-496-5900 Preparer's Name:JACK L. SHENEBERGER

CAGE:71984

=== Contractor Identification ===

Company Name: DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI ZIP:48611 Country:US

Phone:517-496-4388

CAGE:71984

======= Composition/Information on Ingredients ========

Ingred Name: SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7 RTECS #:VV7330000 Fraction by Wt: 17%

OSHA PEL:SEE TABLE Z-3

ACGIH TLV:0.1 MG/M3 RDUST;9495

Ingred

CAS:68083-19-2 Ingred Name: POLYDIMETHYLSILOXANE, HYDROXY TERMINATED CAS:70131-67-8 Other REC Limits: NONE RECOMMENDED ============== Hazards Identification ======================= Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: THE LISTED POTENTIAL EFFECTS OF OVEREXPOSURE ARE BASED ON ACTUAL DATA, STUDIES OF SIMILAR COMPOSITIONS, COMPONENT D ATA AND/OR EXPERT REVIEW OF THE PRODUCT. EYE:TEMPORARY DISCOMFORT, MILD REDNESS. SKIN:NO KNOWN ADVERSE EFFECT. ORAL:LARGE AMOUNT MAY CAUSE G/I DISCOMFORT. INHALED:NO INJURY EXPECTED FOR EXPOSURES 212F,>100C Lower Limits: N.D. Upper Limits:N.D. Extinguishing Media: CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER FOG. Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS & PROTECTIVE CLOTHING SHOULD BE WORN IN FIGHTING FIRES INVOLVING CHEMICALS. Unusual Fire/Explosion Hazard: NONE. Spill Release Procedures: USE ABSORBENT MATERIAL TO COLLECT & CONTAIN. Neutralizing Agent:MFR GAVE NO INFORMATION ON MSDS. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE BELOW 90F/32C. USE REASONABLE Other Precautions:TRACES OF FORMALDEHYDE AND OTHER THERMAL DECOMPOSITION PRODUCTS MAY FORM AT TEMPERATURES ABOVE 302F (150C) IN THE PRESENCE OF A IR. PROVIDE ADEQUATE VENTILATION WHEN HANDLING AT ELEVATED TEMPERATURE. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: NO RESPIRATORY PROTECTION SHOULD BE NEEDED. Ventilation: MECHANICAL (GENERAL) VENTILATION: RECOMMENDED. LOCAL EXHAUST SHOULD NOT BE NEEDED. Protective Gloves:NONE Eye Protection: SAFETY GLASSES AS A MINIMUM Other Protective Equipment: AS REQUIRED Work Hygienic Practices: REMOVE GROSS AMOUNT OF CHEMICAL FROM SKIN AS SOON AS PRA

Name: DIMETHYL SILOXANE, DIMETHYLVINYL TERMINATED

| CTICAL. WASH THOROUGHLY AT MEALTIME & END OF SHIFT |
|---|
| Supplemental Safety and Health |
| MFR LISTED ONLY INGREDIENT #1 IN INGREDIENTS SECTION. THE REMAINDER ARE |
| LISTED W/INDIVIDUAL STATE REGULATIONS. |

========= Physical/Chemical Properties ==========

HCC:N1 NRC/State Lic Num:NONE Vapor Pres: