View NSN Online: https://aerobasegroup.com/nsn/6810-00-006-4205

Product ID: ETHYLENE GLYCOL, MSDS Date:01/01/1987 FSC:6810 NIIN:00-006-4205 MSDS Number: BCVBK === Responsible Party === Company Name: MALLINCKRODT INC., SCIENCE PRODUCTS DIVISION Emergency Phone Num:314 982 5000 CAGE:62910 === Contractor Identification === Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO Address:222 RED SCHOOL LANE Box:City:PHILLIPSBURG State:NJ ZIP:08865 Country:US Phone:908-859-2151 CAGE:62910

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: >99% OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Effects of Overexposure:INH:DIZZ,HEAD,PULMONARY E DEMA;ING:CAUSES VOMIT,HEAD,LOW BLD PR;EYES/SKIN:MINOR/SEVERE IRRITATION.

First Aid:INHAL:RMV TO FRESH AIR.GIVE CPR/OXYGEN IF BREATHING IS DIFFICULT.GET MD;INGEST:IMMED INDUCE VOMIT BY GIVING 2 GL OF WATER.NOTHING BY MOUTH IF UNCONSCIOUS.GET MD IMMED;SKIN/EYES:FLUSH IMMED W/LG QTY H* 20 FOR 15 MIN.RMV CONTMNTD CLOTHES.GET MED ATTN.

Flash Poi

nt:110C(230F) Lower Limits:3.2 Upper Limits:15.3 Extinguishing Media:ALCOHOL FOAM,WATER,CO*2,DRY CHEMICAL.WATER/FOAM MAY FROTH. Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*20 SPRAY TO COOL CONTR. Unusual Fire/Explosion Hazard:MODERATE HAZARD WHEN EXPOSED TO HEAT OR FLAME
======================================
Spill Release Procedures: VENTILATE AREA OF SPILL.CLEAN UP PERSONS NEED PROTCTV CLOTHG/RESP PROTCTION FM VAP.COLLECT LIQUID & PLACE IN A SUITABLE CONTAINER FOR RECOVERY OR DISPOSAL.WASH RESIDUE & SMALL
SPILLS TO SEWER W/COPIOU S AMTS OF WATER.REMOVE ALL SOURCES OF IGNITION.
======================================
 Handling and Storage Precautions: KEEP IN TIGHTLY CLOSED CONTNRS AT COOL,DRY, VENTILATED PLACE. PROTECT AGAINST PHY DAMAGE. Other Precautions: AVOID BREATHING MIST. USE W/ADEQUATE VENTILATION. KEEP CONTAINERS CLOSED. WASH THOROUGHLY AFTER HANDLING. AVOID SKIN, EYES & CLOTH ING CONTACT. DO NOT EAT IN WORK AREA.
======================================
Respiratory Protection:FULL FACE RESPIRATOR Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves:IMPERVIOUS Eye Protection:GOGGLES/FACE SHIELD Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION Supplemental Safety and Health
MSDS FROM MFR DATED 01/28/85,CONFORMS TO OSHA HAZ COMM STD; SP GRAVITY RANGE:1.112-1.115
======================================

al/Chemical Properties ============

HCC:V5 Boiling Pt:=192.8C, 379.F Vapor Pres:.05 Vapor Density:2.14 Spec Gravity:1.1135 Evaporation Rate & amp; Reference:1.0(CCL*4=1) Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQID.ODORLESS

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS,CORROSIVE MATL;OLEUM,H*2SO*4,HCL*4,ETC. Stability Condition to Avoid:IGNITION & MOISTURE SOURCES. Hazardous Decompositi on Products:OXIDES OF NITROGEN & CARBON WHEN IGNITED IN AIR.

Waste Disposal Methods:WHATEVER CANNOT BE SAVED FOR RECLAMATION MAY BE DISPOSD AS HAZ WASTE IN A RCRA APPRVD WASTE DISPOSAL FACILITY OR MIX WITH A MORE FLAMMABLE SOLVENT AND ATOMIZE IN AN APPROVED INCINERATION.ENSURE COMPLI ANCE W/LOCAL,,STATE, & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This in

formation is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.