View NSN Online: https://aerobasegroup.com/nsn/6810-00-006-4205

UNION CHEMICALS DIVISION,UNION OIL COMPANY OF CALI -- AMSCO SOLV 5660 6810-00-006-4205

Product ID: AMSCO SOLV 5660 MSDS Date:01/01/1985 FSC:6810 NIIN:00-006-4205 MSDS Number: BCVBL === Responsible Party === Company Name: UNION CHEMICALS DIVISION, UNION OIL COMPANY OF CALI Emergency Phone Num: (312)885-5450 Preparer's Name:NOT PROVIDED CAGE:DO714 === Contractor Id entification === Company Name: UNION CHEMICALS DIVISION Address:1345 NORTH MEACHAM ROAD Box:7600 City:SCHAUMBURG State:IL ZIP:60196 Phone:213-664-2121 OR 800-424-9300 CAGE:DO714 Company Name: UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN Address:1650 EAST GOLF ROAD Box:City:SCHAUMBURG State:IL ZIP:60195 Country:US Phone:708-619-2644 CAGE:77416

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt : 100% OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

======================================
Effects of Overexposure:MAY IRRITAE EYE & SKIN ON PROLONGED CONTACT,IRRITATE RESPIRATORY TRACT,CNS DEPRESSION.SEE SUPPL DATA
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICA
L ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
======================================
Flash Point:>93.3C, 200.F Extinguishing Media:FOAM,CO*2,DRY CHEMICAL FIRE FIGHTING APPARATUS Fire Fighting Procedures:USE SCBA.DO NOT USE WATER EXCEPT FOR COOLING. Unusual Fire/Explosion Hazard:NONE SPECIFIED BY THE MFGR
======================================
Spill Release Procedures: FLUSH SPILLED MATERIAL INTO SU ITABLE RETAINING AREAS OR CONTAINERS WITH LARGE QUANTITIES OF WATER. SMALL AMOUNTS OF
SPILLED MATERIAL MAY BE ABSORBED INTO AN APPROPRIATE ABSORBANT.
Handling and Storage Precautions: KEEP CONTAINER COOL, DRY & AWAY FROM SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION & KEEP THE CONTAINERS CLOSED WHEN NOT IN USE.

Other Precautions: DO NOT INHALE VAPORS. AVOID EYE & SKIN CONTACT.

======= Exposure Controls/Per

sonal Protection ========

Respiratory Protection:USE NIOSH/MSHA APPROVED CARTRIDGE RESPIRATOR OR GAS MASK FOR THIS PR Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1 Spec Gravity:> H*20 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:COMPLETE Appearance and Odor:CLEAR,LITTLE COLOR,CHARACTERISTIC ODOR Percent Volatiles by Volume:NEGL

Stability Indicator/Materials to Avoid:YES NONE SPECIFIED BY THE MFGR Stability Condition to Avoid:NONE SPECIFIED BY THE MFGR Hazardous Decomposition Products:CO AND/OR CO*2

Waste Disposal Methods: DISPOSE OF THE COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE & FEDERALS REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America i n no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their

particular situation.