View NSN Online: https://aerobasegroup.co.il/nsn/6830-00-079-4694 UNION CARBIDE CORPORATION -- UCON PROPELLANT 11 -- 6830-00-079-4694 Product ID:UCON PROPELLANT 11 MSDS Date:01/01/1985 FSC:6830 NIIN:00-079-4694 MSDS Number: BCXRS === Responsible Party === Company Name: UNION CARBIDE CORPORATION Emergency Phone Num:212-551-4785 CAGE:6M841 === Contractor Identification === Company Name: UNION CARBIDE CORP Address:OLD RIDGEBURY R Box:City:DANBURY

State:CT ZIP:06817 Country:US CAGE:6M841

======= Composition/Information on Ingredients ========

Ingred Name:TRICHLOROFLUOROMETHANE (CFC-11) (SARA III)

CAS:75-69-4

RTECS #:PB6125000 Fraction by Wt: 100% OSHA PEL:1000 PPM

ACGIH TLV:C, 1000 PPM; 9293

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

========== Hazards Identification ===========================

Effects of Overexposure:FROSTBITE.BREATHING CONCENTRATIONS APPROACHING

======================================
First Aid:FLUSH FROSTED AREAS WITH WARM WATER.IF INHALED IN HIGH CONCENTRATIONS, MOVE TO FRESH AIR
======================================
Flash Point:NONE Fire Fighting Procedures:NONE Jnusual Fire/Explosion Hazard:NONE
========= Accidental Release Measures =============
Spill Release Procedures:COVER WITH ABSORBENT MATERIAL(& L DAD INTO WASTE CONTAINER
======================================
Handling and Storage Precautions:CAUTION! LIQUID & GAS UNDER PRESSURE.KEEP AWAY FROM HEAT AND OPEN FLAMES.DO NOT DROP OR REFILL.NON FLAMMABLE LIQUID GAS
====== Exposure Controls/Personal Protection =========
Respiratory Protection:FRESH-AIR MASK FOR HIGH CONCENTRATIONS Ventilation:LOCAL EXHAUST IS PREFERRED.MECHANICAL IS ACCEPTABLE Eye Protection:SAFETY GLASSES
Other Protecti ve Equipment:EYE BATH & SAFETY SHOWER Supplemental Safety and Health
========= Physical/Chemical Properties ============
HCC:N1 Boiling Pt:B.P. Text:74.8F Vapor Pres:13 Vapor Density:4.7 Spec Gravity:1.49
Evaporation Rate & Reference:63 BUTYL ACETATE
Solubility in Water:0.11% Appearance and Odor:WATER-WHITE LIQUID;CHLORINATED SOLVENT ODOR Percent Volatiles by Volume:100
========= Stability and Reactivity Data ===========
Stability Indicator/Materials to A

10% IN AIR WILL CAUSE DIZZINESS & DROWSINESS

======= Disposal Considerations ===========

Waste Disposal Methods:LANDFILL OR MIX IN SMALL PROPORTION WITH BURNABLE LIQUID & INCINERATE UNDER APPROVED CONTROLLED PROCEDURES

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.