View NSN Online: https://aerobasegroup.com/nsn/6505-00-105-0000

MIDWEST SOLVENTS COMPANY OF ILLINOIS -- GRAIN NEUTRAL SPIRITS -- 6505-00-105-0000

Product ID:GRAIN NEUTRAL SPIRITS MSDS Date:01/01/1985 FSC:6505 NIIN:00-105-0000 **MSDS Number: BCYSR** === Responsible Party === Company Name: MIDWEST SOLVENTS COMPANY OF ILLINOIS Address: RIVER RD AND FRONT ST Box:1069 City:PEKIN State:IL ZIP:61555-1069 Country:US **Emergency Phone Num:30** 9-353-3990 CAGE:KO071 === Contractor Identification === Company Name: MIDWEST GRAIN PRODUCTS OF IL Address: RIVER RD AND FRONT ST Box:1069 **City:PEKIN** State:IL ZIP:61555-1069 Country:US Phone:309-353-3990 CAGE:3J969 Company Name: MIDWEST SOLVENTS COMPANY OF ILLINOIS Address: RIVER RD AND FRONT ST Box:1069 City:PEKIN State:IL ZIP:61555-1069 Country:US CAGE:KO071 Ingred Name: ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5 RTECS #:KQ6300000 Frac tion by Wt: 100% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192

======================================
Effects of Overexposure:STUPOR AND DROWSINESS,INTOXICATION.SEE PHYSICIAN.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE
======================================
Flash Point:55F CLOSED CUP Lower Limits:3.28 Upper Limits:19.0 Extinguishing Media:CO*2,DRY CHEMICAL,FOAM. Fire Fighting Procedures:DO NOT USE WATER Unusual Fire/Explosion Hazard:NONE SPECIFIED BY THE MFR.
======================================
Spill Release Procedures: RECOVER THE CONTENT INTO A CONTAINER AFTER FLOODING WITH WATER.
======================================
Handling and Storage Precautions:KEEP AWAY FROM FLAMES;LARGE STORAGE TANKS EQUIPPED WITH FLAME ARRESTORS. PROVIDE ADEQUATE VENTILATION. Other Precautions:AVOID INHALATION. EXPLOSION PROOF PRECAUTIONS.
======================================
Respiratory Protection:USE NIOSH/OSHA APPROVED RESPIRATOR FOR ALCOHOLS. Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN