

TEXACO,INC -- 01592 OUTBOARD & 2-CYCLE ENGINE OIL,50-1 -- 9150-00-117-8791

=====  
Product Identification  
=====

Product ID:01592 OUTBOARD & 2-CYCLE ENGINE OIL,50-1

MSDS Date:01/20/1988

FSC:9150

NIIN:00-117-8791

MSDS Number: BCZQW

=== Responsible Party ===

Company Name:TEXACO,INC

Box:509

City:BEACON

State:NY

ZIP:12508

Country:US

Info Phone Num:914-831-3400,EXT 204

Emergency Phone Num:914-831-3400,EX

T 204

CAGE:KO140

=== Contractor Identification ===

Company Name:TEXACO INC CORPORATE HQ

Address:2000 WESTCHESTER AVE

City:WHITE PLAINS

State:NY

ZIP:10604

Country:US

Phone:914-253-4000

CAGE:59595

Company Name:TEXACO,INC

Box:509

City:BEACON

State:NY

ZIP:12508

Country:US

Phone:914-831-3400,EXT 204

CAGE:KO140

=====  
Composition/Information on Ingredients  
=====

Ingred Name:KEROSINE

CAS:8008-20-6

RTECS #:OA5500000

Minumum % Wt:20.

Maxumum % Wt:35.

Ingred Name:ADDITIVE PKG-ALIPHATIC

CARBOXYLIC ACID AMIDE

Minumum % Wt:11.

Maxumum % Wt:20.

Ingred Name:SOLVENT DEWAXED HEAVY PARAFFINIC PETROLEUM DISTILLATES

CAS:64742-65-0

Minumum % Wt:50.

Maxumum % Wt:65.

OSHA PEL:5 MG/CUM (MIST)

ACGIH TLV:5 MG/CUM (MIST)

Ingred Name:HYDROTREATED C25 BRIGHT STOCK-BASED LUBRICATING OIL

CAS:72623-83-7

Minumum % Wt:4.

Maxumum % Wt:11.

OSHA PEL:5 MG/CUM (MIST)

ACGIH TLV:5 MG/CUM (MIST)

=====  
Hazards Identification  
=====

Effects of Overexposure:INHAL-DROWSINESS  
,NARCOSIS,POSS UNCONSCIOUSNESS  
IN CONFINED SPACE. EYE-MINIMAL IRRITATION. SKIN-IRRITATING W/POSS  
REDNESS,EDEMA,DRYING OF SKIN;POSS DERMATITIS ON PROLONGED/REPEATED  
CONTACT.

=====  
First Aid Measures  
=====

First Aid:INHAL-GET TO FRESH AIR;GIVE ARTIF RESPIR IF NEEDED.  
EYES-FLUSH W/PLENTY WATER. SKIN-WASH AREA W/SOAP & WATER. INGEST-DO  
NOT INDUCE VOMITING,ASPIRATION MAY CAUSE CHEM PNEUMONIA.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:=80.C, 176.F  
Extinguishing Media:WATER SPRAY (ESP TO KEEP CONTNRS COOL), DRY CHEM,  
FOAM, CARBON DIOXIDE  
Fire Fighting Procedures:NONE GIVEN  
Unusual Fire/Explosion Hazard:NONE GIVEN

=====  
Accidental Release Measures  
=====

Spill Release Procedures:VENT AREA;USE SLF-CONTND BREATH  
APPARATUS/SUPPLIED AIR MASK. CONTAIN SPILL IF POSS. WIPE UP OR  
ABSORB ON SUITABLE MATL & SHOVEL UP.

=====

= Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FM HEAT & OPEN FLAME.  
TRANSPORT,HANDLE OR STORE IAW OSHA REG 1910.106.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SUPPLIED AIR RESPIR PROTECT FOR CLEANING LGE  
SPILLS,OR ENTRY INTO TANKS,VESSELS,OTHER CONFINED AREAS.  
Ventilation:ADEQUATE TO MEET COMPONENT PERMISSIBLE CONCENTRATIONS.  
Protective Gloves:YES  
Eye Protection:CHEM GOGGLES OR FACESHIELD OPT  
IONAL  
Other Protective Equipment:TO PREVENT SKIN CONTACT  
Work Hygienic Practices:WASH EXPOSED SKIN AREAS SEVERAL TIMES  
DAILY;CLEAN SOILED CLOTHING AT LEAST WEEKLY.  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V4  
Spec Gravity:0.8751  
Appearance and Odor:DARK,REDDISH PURPLE FLUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG OXIDIZERS  
Hazardous Decomposition Pro  
ducts:OXIDES OF CARBON,ALDEHYDES & KETONES.  
COMBUSTION PRODUCTS OF NITROGEN & SULFUR

===== Disposal Considerations =====

Waste Disposal Methods:PRODUCT,AS PURCHASED,DOES NOT MEET RCRA OF HAZ  
WASTE. MAY BECOME HAZ WASTE DEPENDING ON USE,PROCESSING,MIXING.  
FOLLOW LOCAL,STATE & FED REGS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United

States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.