

SCM-CORP. COATINGS & RESINS PIU. -- 33531 SAND INFRA RED -- 8010-00-133-5904

=====
Product Identification
=====

Product ID:33531 SAND INFRA RED

MSDS Date:01/01/1985

FSC:8010

NIIN:00-133-5904

MSDS Number: BDBCW

=== Responsible Party ===

Company Name:SCM-CORP. COATINGS & RESINS PIU.

Emergency Phone Num:216-344-8000

CAGE:92300

=== Contractor Identification ===

Company Name:SCM-CORP. COATINGS & RES

INS PIU.

CAGE:92300

=====
Composition/Information on Ingredients
=====

Ingred Name:TRIETHYLAMINE (SARA III)

CAS:121-44-8

RTECS #:YE0175000

Fraction by Wt: .09%

OSHA PEL:25 PPM/15 STEL

ACGIH TLV:10 PPM/15 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:DENATURED ALCOHOL

Fraction by Wt: 1%

ACGIH TLV:1000PPM

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 39%

OSHA PEL:100 PPM

Ingred Name:ETHYLBENZENE

RTECS #:

KS5600000
Fraction by Wt: 4%
ACGIH TLV:100PPM

===== Hazards Identification =====

Effects of Overexposure:IRRIT. OF EYES,SKIN,&RESPIRATORY TRACT.POSS.
DERMATITIS ON REPEATED & PROLONGED SKIN CONTACT.POSSI

===== First Aid Measures =====

First Aid:FUMES-MOVE PERSON TO WELL VENTILATED AREA.RESTORE
BREATHING.GET MEDICAL ATTENTION.SKIN CONTACT-WIPE W/CLEAN
CLOTH,WASH THOROUGHLY W/SOAP & WATER.EYE CONTACT-FLUSH THOR
OUGHLY
W/WATER,GET MEDICAL ATTENTION.

===== Fire Fighting Measures =====

Flash Point:50F TCC 10C
Lower Limits:.9
Extinguishing Media:CO*2,DRY CHEMICAL OR FOAM
Fire Fighting Procedures:WATER MAY BE INEFFECTIVE ON FIRE,BUT WATER
SPRAY MAY BE USED
Unusual Fire/Explosion Hazard:KEEP AWAY FROM HEAT,SPARKS & OPEN
FLAME.CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT O

===== Accidental Release Measures =====

Spill
Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE
AREA.MOP SPILLS W/INERT ABSORBENT.BURN SWEEPINGS IN A SAFE AREA.

===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 100F.KEEP CONTAINERS
CLOSED & AWAY FROM HEAT AND OPEN FLAME.
Other Precautions:AVOID PROLONGED CONTACT WITH SKIN & BREATHING VAPORS
OF SPRAY MIST. DO NOT TAKE INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respi

ratory Protection:SPRAY APPLICAT:OPEN AREAS-USE PAINT SPRAY
MASK,MECH. FILTER RESPIRAT

Ventilation:PROVIDE DILUTION VENTILATION OR LOC.EXH.TO KEEP VAPROS
BELOW

Protective Gloves:SOLVENT RESISTE

Eye Protection:SPLASH PROOF GOGGLES INW

Supplemental Safety and Health

WATER MAY BE INEFFECTIVE ON FIRE BUT WATER SPRAY MAY BE USED TO COOL
CLOSED CONTAINERS EXPOSED TO EXTREME HEAT OR FIRE TO PREVENT
PRESSURE BUILD UP & POSSIBLE AUTOIGNITION OR EXPLOSION.

=====
Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:165-290F

Vapor Density:LIGH

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:68.3

=====
Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:CONTAMINATION W/FOREIGN MATERIALS

=====
Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOCAL REGULATIONS.

Disclaimer

er (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.