

BEECHAM HOME IMPROVEMENT PRODUCTS INC -- DAP WELDWOOD CONTACT CEMENT --
8040-00-142-9193

=====
===== Product Identification =====

Product ID:DAP WELDWOOD CONTACT CEMENT

MSDS Date:01/01/1987

FSC:8040

NIIN:00-142-9193

MSDS Number: BDBSG

=== Responsible Party ===

Company Name:BEECHAM HOME IMPROVEMENT PRODUCTS INC

Address:855 N 3RD ST

City:TIPP CITY

State:OH

ZIP:45371-3014

Country:US

CAGE:1BL51

=== Contr

actor Identification ===

Company Name:BEECHAM HOME IMPROVEMENT PRODUCTS INC

Address:855 N 3RD ST

Box:277

City:TIPP CITY

State:OH

ZIP:45371-3014

Country:US

CAGE:1BL51

=====
===== Composition/Information on Ingredients =====

Ingred Name:HEXANE (N-HEXANE)

CAS:110-54-3

RTECS #:MN9275000

Fraction by Wt: -45%

OSHA PEL:500 PPM

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: -28%

OSHA PEL:200 PPM/150 S

TEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: -28%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:ACUTE:ANESTHETIC.CAUSE IRRIT OF THE RESPIR
TRACT,HDACH,DIZZ,NAUSEA OR UNCONSCIOUSNESS.SUPP DATA.

=====
First Aid Measures
=====

First Aid:INHAL:REMOVE TO FRESH AIR,RESTORE BREATH.CONTACT A
PHYSICIAN.EYE:FLUSH W/ LARGE AMOUNTS OF WATER.CONTACT A
PHYSICIAN.SKIN:WASH W/ SOAP & WATER.CONSLT A PHYSICIAN IF IRRIT
DEVELOPS.INGEST:DO NOT INDUCE VOMIT.GIVE WATER OR MILK.CONTACT A
PHYSIC IMMED

=====
Fire Fighting Measures
=====

Flash Point:-50--20F CC
Lower Limits:1.2
Upper Limits:12.8
Extinguishing Media:FOAM,CO*2,DRY CHEMICALS
Fire Fighting Procedures:FULL PROTECT EQ
UIP.SCBA.DO NOT USE STRAIGHT
HOSE H*20 STREAM
Unusual Fire/Explosion Hazard:CONTNR MAY EXPLO IF EXPO TO EXTREME
HEAT.ISOLATE FROM HEAT,FLAMES.DO NOT PUT IN CONTACT W/ OXID MAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:SMALL:USE ABSORB MAT OR SCRAPE UP DRIED MAT &
PLACE INTO CONTAINER.LARGE:WEAR PROTECT EQUIP.ELIMINATE ALL SOURCES
OF IGNIT & VENT AREA.CONTAIN SPILL BY DIKING.ABSRB W/ ABSORB
MAT.WASH W/ NONFLAM SOLVE NT:1,1,

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS AND CAUSTICS

Stability Condition to Avoid: EXCESSIVE HEAT

Hazardous Decomposition Products: NORMAL COMBUSTION PRODUCTS, CO*X, NO*X

===== Disposal Considerations =====

Waste Disposal Methods: DISCARDED SPILL RESIDUE MAY BE INCINERATED. DO NOT INCINERATE SEALED CONTNR. DISPOSE ACCORD TO FED, STATE & LOCAL REGULATIONS. LIQUIDS CANNOT BE DISPOSED OF IN A LANDFILL.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.