View NSN Online: https://aerobasegroup.co.il/nsn/9150-00-145-0112

Product ID:WAY OIL MSDS Date:01/01/1987 FSC:9150 NIIN:00-145-0112 MSDS Number: BDCCW === Responsible Party === Company Name: BATTENFIELD AMERICA, INC. Address:1575 CLINTON ST City:BUFFALO State:NY ZIP:14200 Info Phone Num:716-822-8410 Emergency Phone Num:716-822-8410 Preparer's Name: THOMAS G. MUSILLI CAGE:K O105 === Contractor Identification === Company Name: BATTENFELD AMERICA INC Address:1575 CLINTON ST Box:City:BUFFALO State:NY ZIP:14206 Country:US Phone:716-822-8410 CAGE:61808 Company Name: BATTENFIELD AMERICA, INC. Address:1575 CLINTON ST City:BUFFALO State:NY ZIP:14206 Country:US Phone:716-822-8410 CAGE:KO105 Company Name: OCTAGON PROCESS INC. Address:596 RIVER ROAD Box:City:EDGEWATER State:NJ ZIP:07020 Country:US Phone:201-945-9400 CAGE:82925

======= Composition/Information on Ingredient

Ingred Name:MINERAL OIL CAS:64742-65-0 RTECS #:PY8038500 Fraction by Wt: 50% Other REC Limits:5 MG/M3

Ingred Name:MINERAL OIL CAS:72623-83-7 Fraction by Wt: 44%

Ingred Name:POLYISOBUTYLENE CAS:9003-27-4 RTECS #:UD1010000 Fraction by Wt: 2.0%

Ingred Name:SULFURIZED ISOBUTYLENE CAS:68511-50-2 Fraction by Wt: 1.0%

Ingred Name:LEAD METHYL ESTER CAS:68082-78-0 Fraction by Wt: 3.0%

Routes of Entry: Inhalation:
NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:PRODUCT IS A MILD IRRITANT AND DOES
NOT SENSITIZE. VAPOR PRESSURE IS LOW ENOUGH TO BE NON-HAZARDOUS BY
INHALATION. TOXICITY IS LOW BY INGESTION.
Explanation of Carcinogenicity:MFR CLAIMS NO CARCINOGENITY
Effects of Overexposure:EYE/SKIN:IRRITATION. INHALED:NONE REPORTED.
INGESTION:NONE REPORTED.
Medical Cond Aggravated by Exposure:NONE

====== First Aid Me

First Aid:EYE:FLUSH WITH WATER 15 MIN. SKIN:WASH WITH SOAP & WATER. REMOVE CONTAMINATED CLOTHING & LAUNDER BEFORE REUSE. INHALED:NONE REPORTED. INGESTED:DO NOT INDUCE VOMITING. GET MEDICAL ATTENTION.

Flash Point Method:COC Flash Point:360F/182C Autoignition Temp:Autoignition Temp Text:400F Extinguishing Media:WATER FOG,CARBON DIOXIDE,DRY CHEMICAL,FOAM,EARTH/SAND Fire Fighting Proce

dures:WATER MAY CAUSE FROTHING. Unusual Fire/Explosion Hazard:NONE
======================================
Spill Release Procedures:ABSORB WITH INERT MATERIAL. Neutralizing Agent:NONE
======================================
Handling and Storage Precautions:STORE IN LOW FIRE RISK AREA AWAY FROM OXIDIZERS AND IGNITION SOURCES.
========= Exposure Controls/Personal Protection ====================================
Respiratory Protection:NONE EXPECTED TO
BE NEEDED. Ventilation:NO SPECIAL VENTILATION NECESSARY Protective Gloves:NEOPRENE,POLYETHYLENE Eye Protection:FACE SHIELD IF SPLASH HAZARD IS HIGH Work Hygienic Practices:USE GOOD INDUSTRIAL HYGIENE PRACTICE. Supplemental Safety and Health
======================================
HCC:V6 Boiling Pt:B.P. Text:700F/371C Spec Gravity:0.89 Solubility in Water:NIL Appearance and Odor:FATTY,FLUID,OIL
======================================
S tability Indicator/Materials to Avoid:YES STRONG OXIDIZERS Stability Condition to Avoid:NONE REPORTED Hazardous Decomposition Products:NORMAL PRODUCTS OF COMBUSTION. ====================================
Waste Disposal Methods:DISPOSE I/A/W FEDERAL,STATE,LOCAL REGULATIONS. MFR SUGGESTS INCINERATE.
Disclaimer (provided with this information by the compiling agencies):

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The Unit ed States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.