

ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP -- ALKYD MODIFIED URETHANE --
8010-00-165-4420

===== Product Identification =====

Product ID:ALKYD MODIFIED URETHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-165-4420

MSDS Number: BDDTQ

=== Responsible Party ===

Company Name:ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP

Address:2841 S ASHLAND

City:CHICAGO

State:IL

ZIP:60608-5322

Country:US

Em

ergency Phone Num:312-376-9150

CAGE:60035

=== Contractor Identification ===

Company Name:ENTERPRISE CHEMICAL COATING CO DIV OF INSILCO CORP

Address:2841 S ASHLAND

Box:City:CHICAGO

State:IL

ZIP:60608-5322

Country:US

CAGE:60035

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 55%

OSHA PEL:100 PPM

Ingred Name:RESIN

Fraction by Wt: 45%

===== Hazards Identificatio

n =====

Effects of Overexposure:EXCESSIVE,PROLONGED INHAL MAY RESULT IN
HEADACHE,NAUSEA,AND MILD EYE IRRITATION

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER.CALL DR.SKIN:WIPE RESIN OFF AND WASH
AFFECTED AREA.INGEST:DO NOT INDUCE VOMIT.

===== Fire Fighting Measures =====

Flash Point:42/108 TCC

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM,CO*2,DRY CHEM.SAND.

Fire Fig

hting Procedures:CONTAINERS MAY RUPTURE DUE TO EXCESSIVE HEAT
AND PRESSURE

Unusual Fire/Explosion Hazard:AVOID USE OF WATER.

===== Accidental Release Measures =====

Spill Release Procedures:WITH OR WITHOUT SOLID ABSORBENT,SHOVEL OR SCOOP
INTO CONTAINER.SOLVENT RINSE AND WASH DOWN AREA KEEP WELL
VENTILATED.

===== Handling and Storage =====

Handling and Storage Precautions:AVOID FLAME,HIGH TEMP.STORAGE AND
LOCALIZED

SOLBENT VAPOR BUILD-UP.

Other Precautions:GROUND EQUIP.TO AVOID ELECTRICAL SPARKING.DO NOT TAKE
INTERNALLY AND AVOID PROLONGED CONTACT OR INHAL:

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO NORMALLY NECESSARY

Ventilation:LOCAL:TO REDUCE VAPORS AND REDUCE FIRE HAZARD.

Protective Gloves:NEOPRENE

Eye Protection:SAFETY GOGGLES OR GLASSES

Other Protective Equipment:EQUIP.COMPLYING WITH OSHA 1910.132-135.

Supplemental Safety and Health

=====

=====
Physical/Chemical Properties
=====

HCC:F4

Boiling Pt:B.P. Text:156/313

Vapor Pres:2

Vapor Density:4.9

Spec Gravity:0.89

Evaporation Rate & Reference:TOLUEN=1:0.06

Solubility in Water:NIL

Appearance and Odor:CLEAR,AMBER LIQUID,CHARACTERISTIC ODOR OF MIN.SP

Percent Volatiles by Volume:62

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING MATERIALS

Stability Condition to Avoid:EXPOSURE TO SPA

RK,FLAME OR HIGH TEMP.

Hazardous Decomposition Products:CO,CO*2

=====
Disposal Considerations
=====

Waste Disposal Methods:BURY DRUMS IN APPROVED DUMP OR INCINERATE
RECOVERED MATERIALS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate a
nd

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.