View NSN Online: https://aerobasegroup.com/nsn/8040-00-165-6551

ARMSTRONG PRODUCTS COMPANY -- A-12 PART A -- 8040-00-165-6551

Product ID:A-12 PART A MSDS Date:01/01/1985 FSC:8040 NIIN:00-165-6551 MSDS Number: BDDWL === Responsible Party === Company Name: ARMSTRONG PRODUCTS COMPANY Emergency Phone Num:219-267-3226 CAGE:DO043 === Contractor Identification === Company Name: ARMSTRONG PRODUCTS CO Box:647 City:WARSAW State:IN ZIP:4 6580 Phone:219-267-3226 OR 219-267-5375 CAGE:DO043 Company Name: MORTON THIOKOL, INC; ARMSTRONG PRODUCTS COMPANY Address:407-ARGONNE ROAD Box:647 City:WARSAW State:IN ZIP:46580-3811 Country:US Phone:219-267-3226 CAGE:98911

Ingred Name:EPOXY RESIN Fraction by Wt: 65%

Ingred Name:CALCIUM OXIDE CAS:1305-78-8 RTECS #:EW3100000 Fraction by Wt: >2% OSHA PEL:5 MG/M3 ACGIH TLV:2 MG/M3; 9192

Ingred Name:IRON OXIDE CAS:1309-37-1 RTECS # :NO7400000 Fraction by Wt: >2% OSHA PEL:10 MG/M3 (FE) ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:SILICA RTECS #:VV7320000 Fraction by Wt: >2% ACGIH TLV:20 MPPCF

Ingred Name:ALPHA-ALUMINA (ALUMINUM OXIDE) (EPA LISTS ONLY FIBROUS FORMS) (SARA III) CAS:1344-28-1 RTECS #:BD1200000 Fraction by Wt: >2% OSHA PEL:15 MG/M3 TDUST ACGIH TLV:10 MG/M3 TDUST; 9293

Effects of Overexposure: PRIMARY IRRITATION OF EYES & SKIN

\_\_\_\_\_

First Aid:WASH SKIN WITH SOAP & WATER.FLUSH EYES WITH WATER.

Flash Point:480F;249C COC Extinguishing Media:FOAM,CO\*2,DRY CHEMICAL Fire Fighting Procedures:DO NOT USE WATER. AVOID BREATHING SMOKE Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures: CLEAN WITH CLOTH-OBSERVE FIRE HAZARD IF

SOLVENTS ARE USED.SCOOP UP WITH ABSORBENT MATERIAL

Handling and Storage Precautions: HANDLE IN ACCORDANCE TO HAZARDOUS POTENTIALITIES OF CURING AGENT WHEN MIXED THEREWITH

====== Exposure Controls/Personal Protection ==========

Respiratory Protection:NOT ORDINARILY REQUIRED Ventilation:LOCAL-IF HEATED Protective Gloves:RUBBER Eye Protection:GOGGLES Other Protective Equipment:AS NECESSARY TO AVOID SKIN CONTACT Supplemental Safety and Health

HCC:N1 Spec Gravity:1.35 Solubility in Water:VERY SLIGHT Appearance and Odor:RED-BROWN LIQUID

Stability Indicator/Materials to Avoid:YES SDTRONG OXIDIZING AGENTS Stability Condition to Avoid:PREMATURE REACTION WITH EPOXY CURING AGENTS. ACIDS. Hazardous Decomposition Products:CO,ALDEHYDES Conditions to Avoid Polymerization: EXOTHERMIC REACTION DURING CURE

Waste Disposal Methods: CONTROLLED BURNING OR BURIAL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this d

ocument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.