

CORONADO PAINT CO -- PRIMER,RED LEAD,MIL-P-17545,TYPE 1 -- 8010-00-165-8574

=====
Product Identification
=====

Product ID:PRIMER,RED LEAD,MIL-P-17545,TYPE 1

MSDS Date:01/01/1985

FSC:8010

NIIN:00-165-8574

MSDS Number: BDDYR

=== Responsible Party ===

Company Name:CORONADO PAINT CO

Address:308 OLD COUNTY RD

Box:308

City:EDGEWATER

State:FL

ZIP:32032-1812

Country:US

CAGE:33200

=== Contractor Identific

ation ===

Company Name:CORONADO PAINT COMPANY, INC.

Address:308 OLD COUNTY ROAD

Box:City:EDGEWATER

State:FL

ZIP:32132-1812

Country:US

Phone:904-428-6461

CAGE:33200

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR 1910.1025)

CAS:1314-41-6

RTECS #:OG5425000

Fraction by Wt: 26%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.15 MG/M3(PB); 8990

Ingred Name:CHROMIUM (VI) OXIDE

CAS:1333-82-0

RTECS #:GB6650000

Fraction by Wt: 4.5%

OSHA PEL:C, 0.1 MG/M3 (CRO3)
ACGIH TLV:0.05 MG/M3(CR); 8990

Ingred Name:SILICATES
Fraction by Wt: 22%

Ingred Name:ALKYD RESIN
Fraction by Wt: 24%

Ingred Name:PETROLEUM DISTILLATE
Fraction by Wt: 23.5%
ACGIH TLV:500 PPM (MFR)

=====
Hazards Identification
=====

Effects of Overexposure:EYE: IRRIT.SKIN:DRYING INGESTION: LEAD
POISON.VAPORS: IRRIT.

=====
First Aid Measures
=====

First Aid:EYE: FLUSH WITH WATER 15 MIN.SK
IN:WASH WITH SOAP &
WATER.INGESTION:INDUCE VOMITING,CALL A PHYSICIAN.INHALATION: REMOVE
TO FRESH AIR,GIVE ARTIF RESP IF NEEDED,CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:102F/38C (SETA)
Lower Limits:0.8
Upper Limits:5.0
Extinguishing Media:FOAM,CO*2,DRY CHEMICAL
Fire Fighting Procedures:TREAT AS A CLASS B FIRE
Unusual Fire/Explosion Hazard:VAPORS MAY FORM EXPLOSIVE MIXTURES WITH
AIR

=====
Accidental Release Meas
ures
=====

Spill Release Procedures:FLUSH WITH WATER INTO RETAINING AREA OR
CONTAINER.AVOID EXPOSURE TO SPARKS,FIRES OR HOT METAL.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS OR OPEN
FLAMES.USE WITH ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED
SKIN CONTACT.

Other Precautions:DO NOT TAKE INTERNALLY.

=====
Exposure Controls/Personal Protection
=====

Respiratory P

rotection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:LOCAL EXHAUST
Protective Gloves:YES
Eye Protection:YES
Other Protective Equipment:EYE BATH,SAFETY SHOWER
Supplemental Safety and Health
DEFINITIVE GOVERNMENT SPEC/STD REFERENCE: MS35719-2. PKG: 5 GAL

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315F/157C
Vapor Density:4.9
Spec Gravity:1.54
Evaporation Rate & Reference:0.1 (NBU ACTE)
Solubility in
Water:NEGLIGIBLE
Appearance and Odor:ORANGE OPAQUE LIQUID.PETROLEUM DISTILLATE ODOR
Percent Volatiles by Volume:54

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZERS
Hazardous Decomposition Products:CO & VOLATILE OXIDES OF LEAD AND
CHROMIUM

===== Disposal Considerations =====

Waste Disposal Methods:LANDFILL.DO NOT INCINERATE.

Disclaimer (provided with this information by the com
piling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.