View NSN Online: https://aerobasegroup.com/nsn/8040-00-200-4390

ARMSTRONG PRODUCTS COMPANY INC. -- A-6 -- 8040-00-200-4390

Product ID:A-6 MSDS Date:01/01/1985 FSC:8040 NIIN:00-200-4390 **MSDS Number: BDJGK** === Responsible Party === Company Name: ARMSTRONG PRODUCTS COMPANY INC. Address:407 ARGONNE RD Box:657 City:WARSAW State:IN ZIP:46580-3811 Country:US CAGE:DO043 === Contractor Identification === Company Name: ARMSTRONG PRODUCT S CO Box:647 City:WARSAW State:IN ZIP:46580 Phone:219-267-3226 OR 219-267-5375 CAGE:DO043 Company Name: MORTON THIOKOL, INC; ARMSTRONG PRODUCTS COMPANY Address:407-ARGONNE ROAD Box:647 City:WARSAW State:IN ZIP:46580-3811 Country:US Phone:219-267-3226 CAGE:98911

Ingred Name:EPOXY RESIN Fraction by Wt: 40%

Ingred Name: VINYL RESIN Fraction by Wt: 17%

Ingred Name:FILLER Fraction by Wt: 23%

====== Hazards Identific

Effects of Overexposure:EYE:MINOR IRRIT. SKIN:POSS SENSITIZER & MINOR IRRIT INHAL:POSS PROBLEM WHEN HEATED TO HIGH TEMP.

First Aid:EYES:FLUSH WITH WATER 15 MINUTES. IF ILL EFFECTS DEVELOP,GET MD. SKIN:WASH W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING & WASH THEN BEFORE REUSE. INHAL:REMOVE TO FRESH AIR & GET MD. INGEST;NO KNOWN AN TIDOTE. TREAT SYMPTOMS. W/LG AMTS INDUCE VOMT

====

Flash Point:>135F;57C, TCC Extinguishing Media:FOAM, CO*2 DRY CHEM

Spill Release Procedures:SOAK UP IN ABSORBANT MATERIAL OR SCRAPE UP. RESIDUAL CAN BE REMOVED WITH NON-FLAMMABLE SOLVENT SUCH AS METHYLENE CHLORIDE. IF SOLVENT IS USED ADEQ VENTIL IS REQUIRED.

Handling and Storage Precau tions:PRACTICE CAUTION TO AVOID SKIN AND EYE CONTACT. AVOID BREATHING VAPORS OF HEATED MATERIALS.

Ventilation:MECH TO MAINTAIN BELOW THE TLV. Protective Gloves:YES Eye Protection:SAFETY GLASSES W/SHIELDS. Other Protective Equipment:BARRIER CREAMS HELPFUL. CLEAN BODY COVERING CLOTHING. Supplemental Safety and Health SPEC:TY II. CONTAINER: GALLON CAN

HCC:F4 Boiling Pt:B.P. Text:389F>198C Spec Gravity:0.96 Solubility in Water:NEGLIGIBLE Appearance and Odor:GRAY PASTE

Stability Indicator/Materials to Avoid:YES Conditions to Avoid Polymerization:EXCESS OF HARDENER.

Waste Disposal Methods:SOAK UP IN ABSORBANT MATERIAL OR SCRAPE UP. RESIDUAL CAN BE REMOVED WITH NON-FLAMMABLE SOLVENT SUCH AS METHYLENE CHLORIDE. IF SOLVENT IS USED ADEQ VENTIL IS REQUIRED.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suita bility of this information to their particular situation.