View NSN Online: https://aerobasegroup.com/nsn/9150-00-211-6057

MOBIL OIL CORP -- MOBIL AERO HFA -- 9160-00-211-6057

Product ID:MOBIL AERO HFA

MSDS Date:12/02/1985

FSC:9160

NIIN:00-211-6057

MSDS Number: BDJRX === Responsible Party ===

Company Name: MOBIL OIL CORP

Address:150 E 42ND ST

City:NEW YORK

State:NY

ZIP:10017-5612 Country:US

Info Phone Num:212-883-4242

Emergency Phone Num:212-883-4411/800-424-9300(CHEMTREC)

Preparer's

Name: ENVIRO AFF & TOXIC DEPT

CAGE:1E969

=== Contractor Identification === Company Name:MOBIL CORP

Address:150 E 42ND ST Box:City:NEW YORK

State:NY

ZIP:10017-5612

Country:US

Phone:212-883-4242

CAGE:57635

Company Name: MOBIL OIL CORP

Address:530 EAST SWEDESFORD ROAD

Box:1031

City: VALLEY FORGE

State:PA ZIP:19482 Country:US

Phone:703-849-3265

CAGE:1E969

Company Name: MOBIL OIL CORP, NORTH AMERICAS MARKETING AND REFINING

Address:3225 GALLOWS ROAD

Box:City:FAIRFAX

State:VA ZIP:22037 Country:US Phone:80 0-662-4525/856-224-4644 CAGE:3U728 Company Name: MOORE SCALE SERVICE CAGE:2E019 ====== Composition/Information on Ingredients ======== Ingred Name: REFINED MINERAL OIL Fraction by Wt: >85% Other REC Limits: NONE RECOMME Ingred Name: ADDITIVES AND/OR OTHER INGREDIENTS Fraction by Wt: 5G/KG (SEE SUPPLEMENTAL) Routes of Entry: Inhalation:NO Skin:YES Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic: ACUTE: SKIN: MODERATE IRRITATION. EYE:SLIGHT IRRITATION. CHRONIC:PROLONGED REPEATED SKIN CONTACT WITH LOW VISCOSITY OILS MAY LEAD TO DISSOLVING NATURAL OILS FROM THE SKIN CAUSING IRRITATION. Effects of Overexposure:EYE/SKIN:REDNESS, DISCOMFORT. Medical Cond Aggravated by Exposure: NONE SPECIFIED BY MANUFACTURER. First Aid:EYE:FLUSH W/WATER FOR @ LEAST 15MINS. SKIN:WASH AREA W/SOAP & WATER. REMOVE CONTAMINATED CLOTHING. INHAL: NOT EXPECTED TO BE A PROBLEM, INGEST: DO NOT INDUCE VOMITING, ADMINISTER VEGETABLE OIL. GET MED ATTN. (NOTE TO PHYSICIAN: MATERIAL IS ASPIRATED INTO LUNGS MAY CAUSE CHEMICAL PNEUMONITIS. TREAT APPROPRIATELY.). ============= Fire Fighting Measures ======================== Flash Point: 205F, 96C (COC)

Lower Limits:0.6 Upper Limits:7.0

Extinguishing Media:CO\*2,FOAM,DRY CHEM & WATER FOG
Fire Fighting Procedures:USE SCBA & PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard: NONE SPECIFIED BY MANUFACTURER.

======== Accidental Release Measures ==========
Spill Release Procedures:REPORT SPILLS TO APPROPRIATE AUTHORITIES. IF REACHES WATERWAY INCLUDING INTERMITTENT DRY CREEKS CALL US COAST GUARD:800-424-8802. ADSORB ON FIRE RETARDANT TREATED SAWDUST, DIATOMACEOUS EARTH, ETC. SHO VEL UP & DISPOSE.  Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
=========== Handling and Storage ==============
Handling and Storage Precautions:AVOID CONTACT WITH SK IN. FOR INDUSTRIAL USE ONLY. NOT INTENDED OR SUITABLE FOR USE IN OR AROUND A HOUSEHOLD OR DWELLING. Other Precautions:EMPTY CONTAINERS MAY CONTAIN PRODUCT RESIDUE INCLUDING FLAMMABLE OR EXPLOSIVE VAPORS. DO NOT CUT, PUNCTURE, WELD ON OR NEAR CONTAINER. ALL LABEL WARNINGS & PRECAUTIONS MUST BE OBSERVED TIL CONTAINER H AS BEEN THOROUGHLY CLEANED OR DESTROYED.
====== Exposure Controls/Personal Protection ========
Respiratory Protection:NO SPECIAL REQUIREMENTS UND ER ORDINARY CONDITIONS OF USE AND WITH ADEQUATE VENTILATION. Ventilation:NO SPECIAL REQMTS UNDER ORDINARY CONDITIONS OF USE & W/ADEQUATE VENTILATION. USE IN WELL VENTILATED AREA AWAY FROM IGNIT Protective Gloves:IMPERVIOUS Eye Protection:SAFETY GLASSES W/SHIELDS. Other Protective Equipment:EYE WASH/SAFETY SHOWER Work Hygienic Practices:WASH HANDS THOROUGHLY AFTER HANDLING. LAUNDRY CONTAMINATED CLOTHING. Supplemental Safety and Health LD50 IS ESTIMATED BASED ON TESTING OF SIMILAR PROD UCTS &/OR COMPONENTS. FURTHER INFO CONTACT PRODUCT FORMULATION & QUALITY CTRL 703-849-3265.
========== Physical/Chemical Properties ============

HCC:N1

Boiling Pt:B.P. Text:>450F,>232C Vapor Pres: