

THE INDIUM CORPORATION OF AMERICA -- INDALLOY FLUX #5R -- 3439-00-220-3827

=====
Product Identification
=====

Product ID:INDALLOY FLUX #5R

MSDS Date:01/01/1987

FSC:3439

NIIN:00-220-3827

MSDS Number: BDJTJ

=== Responsible Party ===

Company Name:THE INDIUM CORPORATION OF AMERICA

Address:1676-80 LINCOLN AVE

City:UTICA

State:NY

ZIP:13502

Country:US

Emergency Phone Num:315-768-6400

CAGE:KO636

=== Cont

actor Identification ===

Company Name:INDIUM CORP OF AMERICA

Address:1676-80 LINCOLN AVE

Box:City:UTICA

State:NY

ZIP:13502

Country:US

Phone:315-768-6400

CAGE:74858

Company Name:THE INDIUM CORPORATION OF AMERICA

Address:1676-80 LINCOLN AVE

Box:City:UTICA

State:NY

ZIP:13502

Country:US

CAGE:KO636

=====
Composition/Information on Ingredients
=====

Ingred Name:ROSIN

Fraction by Wt: 37%

Ingred Name:ALCOHOLS (TYPE NOT SPECIFIED)

Fraction by Wt: 63%

ACGIH TLV:980 MG/CUM

=====

==== Hazards Identification =====

Effects of Overexposure:LOCAL IRRIT. HIGH CONCENTRATIONS IS NARCOTIC,
CAN CAUSE EYE DAMAGE.

==== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

==== Fire Fighting Measures ===

=====

Flash Point:53F, 11.6C TCC

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.

Unusual Fire/Explosion Hazard:NONE NOTED BY MANUFACTURER.

==== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES. STOP LEAK.
EVACUATE AREA.DO NOT TOUCH SPILLAGE. SM SPILL:ABSORB W. INERT
ABSORBENT. PLACE IN CLOSED CONTAINER. FLUSH AREA W. WATER. LG
SPI

LL: DIKE AHEAD FOR LATER DISPOSAL. NOTIFY AUTHORITIES.

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:AVOID INHALATION OF VAPORS/MIST.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MFR. NIOSH/MSHA APPROVED RESP
IF REQD

V

entilation:MECHANICAL REQD, LOCAL RECOMMENDED
Protective Gloves:LEATHER WORK
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS & LEGS.
Supplemental Safety and Health
MSDS NOT DATED

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:176F,80C
Vapor Pres:33
Spec Gravity:0.875
Solubility in Water:APPRECIABLE
Appearance and Odor:YELLOW BROWN LIQUID, ALCOHOLIC ODOR
Percent Volatiles by Volume:65%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG OXIDIZING AGENTS.
Stability Condition to Avoid:HEAT, IGNITION SOURCES
Hazardous Decomposition Products:CO*2, CO

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE I/A/W ALL LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements
of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.