

CON-LUX COATINGS INC -- TT-P-86G, TY 1, RED LEAD BASE READY-MIXED -- 8010-00-244-5791  
===== Product Identification =====

Product ID:TT-P-86G, TY 1, RED LEAD BASE READY-MIXED

MSDS Date:01/01/1985

FSC:8010

NIIN:00-244-5791

MSDS Number: BDNCX

=== Responsible Party ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:908

-287-4000 / FAX 908-287-9288

Emergency Phone Num:908-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 6.6%

OSHA PEL:100 PPM

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CF

R 1910.1025)  
CAS:1314-41-6  
RTECS #:OG5425000  
Fraction by Wt: 77.3%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3(PB); 8990

===== Hazards Identification =====

Effects of Overexposure:EYES/SKIN:IRRIT. INH:IRRITATE RESP TRACT, HDCH,  
DIZZINESS (INDICATIVE OF SOLVENT BASE PRODUCTS)

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH W/PLENTY OF WATER 15 MINS. INH:MOVE TO FRESH  
AIR. IF ANY IRRITATION PERSISTS, CONSULT MD.

===== Fire Fighting Measures =====

Flash Point:105F,41C TCC  
Lower Limits:1.0  
Upper Limits:6.0  
Extinguishing Media:CO\*2, DRY CHEMICAL, FOAM. H\*2O SPRAY POSS INEFFECTIVE.  
Fire Fighting Procedures:USE H\*2O TO COOL CLSD CNTNR, PRVNT PRESS BLD-UP  
& AUTOIGNITN.  
Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY EXPLODE WHEN EXPOSED TO  
EXTREME HEAT.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES  
OF IGNITION (FLAMES, HOT  
SURFACES, ELECTRICAL STATIC OR FRICTIONAL SPARKS). AVOID BREATHING  
OF VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING  
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP  
AWAY FROM OPEN FLAMES & SPARKS. DO NOT APPLY TO HOT SURFACES. KEEP  
CONTAINERS TIGHTLY CLOSED.  
Other Precautions:DO NOT TAKE INTERNALLY. CONTAINERS SHOULD BE GROUNDED  
WHEN POURING

NG. AVOID PROLONGED OR REPEATED CONTACT W/SKIN.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD CHEMICAL-MECHANICAL FILTER  
RESP.

Ventilation:LOC EXHST TO KEEP TLV BELOW ACCEPTABEL LIMIT.

Protective Gloves:PRLNG/RPTD CNTC

Eye Protection:SPLASH-PROOF SFTY EYEWEAR

Other Protective Equipment:PREVENT PROLONGED CONTACT W/CONTAMINATED  
CLOTHING.

Supplemental Safety and Health  
CONTAINER SIZE: 1 GAL CAN.

=====  
===== Physical/C  
hemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres:2.0

Vapor Density:4.9

Spec Gravity:2.94

Evaporation Rate & Reference: