

OCTAGON PROCESS INC. -- WATCH RINSING SOLUTION, O-C-435, TYPE 2 -- 6850-00-270-9971
===== Product Identification =====

Product ID:WATCH RINSING SOLUTION, O-C-435, TYPE 2

MSDS Date:06/18/1990

FSC:6850

NIIN:00-270-9971

MSDS Number: BDRVH

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020-1105

Country:US

Info Phone Num:201-945-9400

Em

ergency Phone Num:201-945-9400

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:HYDROTREATED HEAVY NAPHTHA

CAS:64742-48-9

Other REC Limits:NONE SPECIFIED

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Other REC Limits:NONE SPECIFIED

OSHA PEL:S,200 PPM

A

CGIH TLV:S, 5 PPM; 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATING TO SKIN/EYES, NOSE,
THROAT AND RESPIRATORY TRACT. CHRONIC:DEFATTING OF SKIN. HIGH VAPOR
CONCENTRATIONS MAY RESULT IN LOSS OF CONSCIOUSNESS AND EVEN DEATH.
ASPIRATION INTO LUNGS MAY RE SULT IN
ASPIRATION PNEUMONITIS.

Effects of Overexposure:GIDDINESS, HEADACHE, NAUSEA. CNS DEPRESSION.

REDNESS OF SKIN AND EYES. IF INGESTED: COUGHING, LABORED BREATHING.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

===== First Aid Measures =====

First Aid:EYES/SKIN:FLUSH WITH WATER FOR AT LEAST 15 MIN. IF IRRITATION
PERSISTS, GET MEDICAL ATTENTION. INHALATION:REMOVE TO FRESH AIR.
RESCITATE IF NECESSARY. GET MEDICAL AID. INGESTION:GET MEDICAL
AID.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:100F/38C

Extinguishing Media:CO*2, FOAM, DRY CHEM.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE FOR FIGHTING FIRE.

USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL. WEAR PROTECTIVE
GEAR, INCLUDING SCBA.

Unusual Fire/Explosion Hazard:NONE.

===== Accidental Release Measures =====

Spill Release Procedures:DIKE AREA TO CONTAIN. SHUT OFF IGNITION

SOURCES. VACUUM UP AND RECOVER IF POSSIBLE. ABSORB RESIDUAL TRACES
WITH SUITABLE ABSORBENT, PLACE IN VESSEL FOR SUBSEQUENT DISPOSAL.
DO NOT ALLOW MATERIAL TO EN TER SEWERS, DRAINS OR WATERWAYS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED

AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED

Other Precautions:DO NOT REUSE SOLUTION ONCE REMOVED FROM C

CONTAINER.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS, ATMOSPHERE-SUPPLYING
RESPIRATOR (29 CFR 1910.134)

Ventilation:MECHANICAL(GENERAL)

Protective Gloves:RUBBER,POLYVINYL ALCOHOL

Eye Protection:GOGGLES,FACESHIELD

Other Protective Equipment:SAFETY SHOES,RUBBER APRON,SKIN BARRIER
CREAM.

Work Hygienic Practices:WASH HANDS AND FACE AFTER USING. LAUNDER
CONTAMINATED CLOTHING BEFORE RE-USE.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:298F/148C

Vapor Pres:10

Spec Gravity:0.78

Evaporation Rate & Reference: