View NSN Online: https://aerobasegroup.com/nsn/8040-00-275-8100 NORTECH ADHESIVE CORP -- NORTECH 2109 -- 8040-00-275-8100 ============= Product Identification ======================== Product ID:NORTECH 2109 MSDS Date:01/01/1985 FSC:8040 NIIN:00-275-8100 MSDS Number: BDSHH === Responsible Party === Company Name: NORTECH ADHESIVE CORP Emergency Phone Num:201-653-8647 CAGE:0GD30 === Contractor Identification === Company Name: MILITARY SPECIFICATIONS PROMULGATED BY MILITARY Address:DEPTS/AG **ENCIES UNDER AUTH OF DEF STD Box:MANUAL** City:4120 3-M Phone:804-279-4371 DSN 695-4371 CAGE:81349 Company Name: NORTECH ADHESIVE CORP Address:136 HALLADAY STREET Box:5256 City: JERSEY CITY State:NJ ZIP:07305 Country:US Phone:201-433-3766 CAGE:0GD30 ======= Composition/Information on Ingredients ======== Ingred Name:SOLVENTS Fraction by Wt: 70% ACGIH TLV:100PPM Ingred Name: POLYMERS Fraction by Wt: 30% =========== Hazards Identification ========================== Effects of O

RESPIRATORY TRACT First Aid: FOR SKIN CONTACT WASH W/WATER AND SOAP. FOR EYE CONTACT WASH W/WATER AND CALL A DR. FOR EXCESSIVE INHALATION, REMOVE TO FRESH AIR AND ADMINISTER OXYGEN IF NECESSARY =========== Fire Fighting Measures ========================== Flash Point: 20F TCC -6.6C Lower Limits: 1.8 **Upper Limits:1.5** Extinguishing Media:FOG,FOAM,DRY CHEMICAL OR CO<sub>2</sub>. Fire Fighting Procedures: HANDLE AS VERY FLAMMABLE LIQUID ======== Accidental Release Measures =========== Spill Release Procedures: ABSORBENT CLEANING SOLVENT ============ Handling and Storage =========================== Handling and Storage Precautions: AVOID OPEN FLAMES AND SPARK SOURCES. PROVIDE ADEQUATE VENTILATION. AVOID EXCESSIVE HEAT. ====== Exposure Controls/Personal Protection ======== Respiratory Protection: RESPIRATORY APPROVED FOR O **RGANIC SOLVENT** Ventilation: AS REQUIRED Protective Gloves: RUBBER OR POLYE Eye Protection: GOGGLES TO PREVENT EYE CO Supplemental Safety and Health ======== Physical/Chemical Properties =========== Boiling Pt:B.P. Text:132 Vapor Pres:186 Spec Gravity:.70 Evaporation Rate & Dr. Reference: 5.0 Solubility in Water: INSOLUBLE Appearance and Odor: AMBER COLOR LIQUID ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES Stabilit

verexposure: CAN CAUSE IRRITATION TO EYES, SKIN AND

 Disposal Considerations	

Waste Disposal Methods: FOLLOW FEDERAL AND LOCAL APPROVED ENVIRONMENT REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all li

y Condition to Avoid:HEAT, SPARKS & OPEN FLAMES.

ability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.