View NSN Online: https://aerobasegroup.com/nsn/8010-00-285-4863

CORONADO PAINT CO -- BROWN -- 8010-00-285-4863

Product ID:BROWN MSDS Date:01/01/1987 FSC:8010 NIIN:00-285-4863 **MSDS Number: BDTPT** === Responsible Party === Company Name: CORONADO PAINT CO Address:308 OLD COUNTY RD Box:308 City:EDGEWATER State:FL ZIP:32032-1812 Country:US Info Phone Num:904-428-6461 / FAX 904-427-7130 Emergency Phone Num:904-428-6461 CAGE:33200 == = Contractor Identification === Company Name: CORONADO PAINT COMPANY, INC. Address:308 OLD COUNTY ROAD Box:City:EDGEWATER State:FL ZIP:32132-1812 Country:US Phone:904-428-6461 CAGE:33200 Ingred Name: ALKYD RESIN Fraction by Wt: 26.8% Ingred Name: PETROLEUM DISTILLATES (NAPHTHA OR RUBBER SOLVENT) CAS:8002-05-9 RTECS #:SE7449000 Fraction by Wt: 26.9% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 8990

======= Hazards Identif

Effects of Overexposure: PRODUCES SEVERE IRRITATION DRYING OF SKIN EXCESSIVE INHALATION CAUSES HEADACHE, DIZZINESS NAUSEA.

First Aid:EYE CONTACT FLUSH W/ WATER,SKIN CONTACT WASH W/ MILD SOAP & WATER & APPLY SKIN CREAM. INHALATION REMOVE TO FRESH AIR AND CALL MD. APPLY ARTIFICIAL RESPIRATION, IF NECESSARY.

Flash Poin t:102F SETA Lower Limits:0.8 Upper Limits:5.0 Extinguishing Media:FOAM CARBON DIOXIDE DRY CHEMICAL. Fire Fighting Procedures:TREAT AS CLASS B FIRE Unusual Fire/Explosion Hazard:VAPOR MAY EXPLODE WHEN MIX WITH AIR

Spill Release Procedures:WEAR A RESPIRATOR FLUSH WITH WATER INTO RETAINING AREA OR CONTAINER. AVOID EXPOSURE TO SPARKS,FIRE OR HOT METAL SURFACE.

=====

Handling and Storage Precautions: KEEP AWAY FROM HEAT, SPARKS, OPEN FLAME.USE WITH ADEAUATE VENTILATION. AVOID PROLONGED OR REPEATED SKIN CONTACT.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:SELF CONTAINED NIOSH APPROVED RESPIRATOR IF NECESSARY. Ventilation:KEEP AWAY FROM HEAT Protective Gloves:NIOSH APPROVED Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:EYE BATH & SAFETY SHOWER. Supplemental Safety and Health

=====

HCC:F4 Boiling Pt:B.P. Text:315 F 157 C Vapor Pres:80 Vapor Density:4.9 Spec Gravity:0.903 Evaporation Rate & amp; Reference:SLOWER THAN NBUACT Solubility in Water:INSOLUBLE Appearance and Odor:PETROLEUM DISTILLATE ODOR BROWN OPAQUE LIQUID Percent Volatiles by Volume:64.0

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZERS. Stability Condition to Avoid:EXCE SSIVE HEAT,SPARK, OPEN FLAMES. Hazardous Decomposition Products:THERMAL DECOMPOSITION MAY YIELD CARBON MONOXIDE.

Waste Disposal Methods:LANDFILL, INCINERATION UNDER SAFE SUPERVISED CONDITIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or impl ied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their particular situation.