

CULLIGAN DESICCANTS DIV OF CULLIGAN INTERNATIONAL -- LITHOGRAPHIC BLANKET ROLLER WASH -- 6850-00-291-0963

===== Product Identification =====

Product ID:LITHOGRAPHIC BLANKET ROLLER WASH

MSDS Date:01/01/1987

FSC:6850

NIIN:00-291-0963

MSDS Number: BDV KR

=== Responsible Party ===

Company Name:CULLIGAN DESICCANTS DIV OF CULLIGAN INTERNATIONAL

Address:3633 UNIVERSITY PKY

Box:431

City:SAN BERNARDINO

S

tate:CA

ZIP:92402

Country:US

Info Phone Num:714-887-2557 / FAX 714-887-2563

Emergency Phone Num:714-887-2557

CAGE:8K833

=== Contractor Identification ===

Company Name:CHEMICAL SPECIALISTS AND DEVELOPMENT INC

Address:2210 HACKBERRY LN

Box:687

City:CONROE

State:TX

ZIP:77305

Country:US

Phone:409-756-1065

CAGE:4N760

Company Name:CULLIGAN DESICCANTS DIV OF CULLIGAN INTERNATIONAL

Address:3633 UNIVERSITY PKY

Box:431

City:SAN BERNARDINO

State:CA

ZIP:92402

Country:US

Phone:714-887-2557

CAGE:8K833

=====

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS
CAS:64475-85-0
RTECS #:PY8240000
Fraction by Wt: 100%
ACGIH TLV:350PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHAL OF HIGH VAPOR CONCENTRAT MAY HAVE RESULTS RANGING FR DIZZI & HEADNESS TO UNCONSCIOUSNESS.

=====
First Aid Measures
=====

First Aid:IF OVERCOME BY VAPOR,REMOVE FROM EXPOS R IMMED;CALL A DR.IF

BREATHING IS IRREG OR STOPPED,START RESUSCITATION,ADMIN. OXYGEN.IF INGESTED,DO NOT INDUCE VOMITING,CALL A DR.IN CASE OF SKIN CONTACT,REMOVE A NY CONTAMINATED CLOTHING.

=====
Fire Fighting Measures
=====

Flash Point:108F TCC 42C T

Lower Limits:0.9%

Upper Limits:6.0%

Extinguishing Media:FOAM,DRY CHEM,CO*2 OR WATER FOG OR SPRAY.

Fire Fighting Procedures:AIR-SUPPLIED BREATHNG EQPMT F/ENC AREAS.COOL EXPOS CONTNR

Unusual Fire/Explosion Hazard:DO NOT MI

X OR STORE W/STRONG OXIDANTS

LIKE LIQUID CHLORIDE OR CONCENTRAT OXYGEN.COMBUSTIBLE LIQUID.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOV ALL IGNIT SOURCES.KP PEOPLE AWAY.RECOVER FREE LIQUID,ADD ABSORBENT (SAND,EARTH,SAWDUST,ETC.) TO SPILL AREA.AVOID BREATHING VAPORS.VENTILAT CONFINED SPACES.OPN ALL WINDOWS/DOORS.KP PETROL PRODCTS OUT OF SEWERS/WATRCOURSES BY DIKING ORIMPOUNDING

=====
Handling and Storag
=====

e =====

Handling and Storage Precautions:KP CONTNRS CLOS WHN NOT IN USE.DO NOT HANDLE OR STORE NEAR HEAT,SPARKS,FLAME OR STRONG OXIDANTS.ADEQ*VENT REQD.*ADEQ MEANS EQUIVAL TO OUTDOORS.

Other Precautions:AVD BREATHING VAPORS.AVOID PROLNG/REPEAT CONTCT WITH SKIN.REMOV CONTAM CLOTHNG,LAUNDR BEFORE REUSE.REUSE CONTAM SHOES & THORO DRY BEFORE REUSE.WASH SKN THORO WITH SOAP/WATR AFTER CONTACT.

===== Exposure Controls/Personal Protection =====

Resp

iratory Protection:USE HYDROCARBN VAP CANISTR OR SUPPLIED-AIR RESPIRATORY PROTCT IN CON

Ventilation:LOC EXHAUS-FACE VELOCITY>60 FPM,USE ONLY W/ADEQ VENTIL

Protective Gloves:CHEM-RESISTANT

Eye Protection:SPLASH GOGG OR FACE SHIEL

Other Protective Equipment:CHEM-RESISTANT APRON RECOMMENDED

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:300F,149C

Vapor Pres: