BRAY OIL CMPANY,INC BRAYCO 855D 9150-00-292-9687 ====================================
======================================
Product ID:BRAYCO 855D MSDS Date:01/01/1987 FSC:9150
NIIN:00-292-9687 MSDS Number: BDVSN
=== Responsible Party === Company Name:BRAY OIL CMPANY,INC. Emergency Phone Num:714-660-9414 CAGE:LO213
=== Contractor Identification === Company Name:BRAY OIL CMPANY,INC. CAGE:LO213
Company Name:CASTROL INDUSTRIAL NORT H AMERICA INC. Address:5511 DISTRICT BLVD Box:City:LOS ANGELES
State:CA ZIP:90040 Country:US Phone:213-890-4420 CAGE:98308
======= Composition/Information on Ingredients ========
Ingred Name:LUBRICATING OIL (SYNTHETIC HYDROCARBONS)TAKE TLV AS OIL MIST SMG/CUM Fraction by Wt: >98% ACGIH TLV:5MG/CUM(OILMIST
======================================
Effects of Overexposure:MAY CAUSE EYES IRRITATION,RESPIRATORY TRACT IRRITATION;PROLONGED SKIN CONTA CT MAY CAUSE DERMATITIS.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.
======================================
Flash Point:325F/163C(COC) Extinguishing Media:DRY CHEMICAL,CO*2,FOAM,WATER FOG. Fire Fighting Procedures:DO NO

View NSN Online: https://aerobasegroup.com/nsn/9150-00-292-9687

T USE DIRECT WATER STREAM.USE SCBA IN COFINED AREA.
Unusual Fire/Explosion Hazard:NONE NOTED.
======== Accidental Release Measures =========
Spill Release Procedures:USE PROPER PERSONAL PROTECTION.WIPE,MOP UP OR USE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.
============ Handling and Storage =============
Handling and Storage Precautions:STORE AT ROOM TEMPERATURE. AVOID HEAT,OPEN FLAMES.KEEP CONTAINER CLOSED WHEN NOT IN USE. Other
Precautions: AVOID SKIN AND EYES CONTACT. WASH THOROUGHLY AFTER EACH USE.
====== Exposure Controls/Personal Protection =======
Respiratory Protection:USE NIOSH APPROVED RESPIRATOR FOR OIL MIST OR VAPORS.
Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION
Protective Gloves:RUBBER Eye Protection:SAFETY/CHEM GOGGLES Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT. Supplemental Safety and Health MSDS DATED J UNE,1979
========= Physical/Chemical Properties =========
HCC:V6 Boiling Pt:B.P. Text:>400F/204C Spec Gravity:0.827 Solubility in Water:NEGLIBLE Appearance and Odor:DEEP RED WINE COLORED OIL LIQUID,PETRO ODOR.
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT,OPEN FLAMES Hazardous Decomposition Products:COMBUSTION:CO AND CO*2.
======== Disp

osal Considerations =========

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL ACCORDANCE WITH LOCAL STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

cument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.