View NSN Online: https://aerobasegroup.com/nsn/6850-00-292-9780 THE LUBRIZOL CORPORATION -- 541; MIL-I-25017 -- 6850-00-292-9780 ============= Product Identification ======================== Product ID:541;MIL-I-25017

MSDS Date:01/01/1985

FSC:6850

NIIN:00-292-9780

MSDS Number: BDVSX === Responsible Party ===

Company Name: THE LUBRIZOL CORPORATION

Address:29400 LAKELAND BLVD

City:WICKLIFFE

State:OH

ZIP:44092-2201 Country:US CAGE:GO887

=== Contractor Identification ===

Company Name:LUBRIZO

L CORP

Address:29400 LAKELAND BLVD

Box:City:WICKLIFFE

State:OH

ZIP:44092-2201 Country:US

Phone:216-943-4200

CAGE:05238

Company Name: THE LUBRIZOL CORP.

CAGE:GO887

======= Composition/Information on Ingredients ========

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000 Fraction by Wt: 37%.

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

========= Hazards Identification ==========

Effects of Overexposure:MAY CAUSE EYE IRRITATION. NOT EXPECTED TO BE PRIMARY SKIN IRRITANT. BUT AVOID PRLNGD OR RPTD CONTACT
======================================
First Aid:EYES: IMMED FLUSH W/PLENTY OF WATER AT LEAST 15 MIN. CALL A PHYSICIAN. WASH HANDS THOROUGHLY AFTER HANDLING.
======================================
Flash Point:80 F PMCC Extinguishing Media:CO*2, DRY CHEMICAL, FOAM Unusual Fire/Explosion Hazard:CAU TION! FLAMMABLE! AVOID EXCESSIVE HEAT, SPARKS, AND OPEN FLAME
========= Accidental Release Measures ==========
Spill Release Procedures:HANDLE AS AN OIL SPILL. USE ADEQUATE VENTILATION. AVOID BREATHING VAPORS.
============= Handling and Storage ==============
Handling and Storage Precautions:STORE AT TEMP BELOW FLASH PT. PRODUCT CONTAINS FLAMMABLE SOLVENT. USE ADEQUATE VENTILATION & AVOID BRTHNG VAPORS OR MIST. STORE IN COOL, DRY PLACE.
her Precautions:KEEP CONTAINERS TIGHTLY CLSD. AVOID CONTACT W/EYES. AVOID PRLNGD OR RPTD CONTACT W/ THE SKIN. WASH HANDS THOROUGHLY AFTER HANDLING
===== Exposure Controls/Personal Protection =======
Ventilation:MFR RECM LOCAL EXHAUST & MECHANICAL VENTILATION Protective Gloves:PLASTIC, RUBBER Eye Protection:SAFETY GLASSES Supplemental Safety and Health
========= Physical/Chemical Properties ==========
HCC:F4 NRC/State Lic Num:NA Spec Gravity:0.960 So

======================================	lubility in Water:NEGLIGIBLE Appearance and Odor:MED BROWN COLORED LIQ W/SOLVENT TYPE ODOR.	
	=========== Stability and Reactivity Data ==================================	

STRONG OXIDIZING AGENTS
Stability Condition to Avoid:TEMPERATURES GREATER THAN FLASH PT (80F, PMCC)

Hazardous Decomposition Products:OXIDES OF CARBON FROM BURNING OR THERMAL DECOMPOSITION.

======= Disposal Considerations ===========

Waste Disposal Methods:CHEMI
CAL WASTE DISPOSAL IS GOVERNED BY THE
RESOURCES CONSERVATION & RECOVERY ACT AS WELL AS BY OTHER LOCAL,
STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.