View NSN Online: https://aerobasegroup.com/nsn/6850-00-292-9780

UOP INC -- UNICOR, TYPE J, CORROSION INHIBITOR -- 6850-00-292-9780

Product ID:UNICOR, TYPE J, CORROSION INHIBITOR MSDS Date:01/01/1989 FSC:6850 NIIN:00-292-9780 MSDS Number: BDVSY === Responsible Party === Company Name:UOP INC Address:25 E ALGONQUIN RD City: DES PLAINES State:IL ZIP:60017-5017 Country:US Info Phone Num:708-391-2123 Emergency Phone Num:708-391-212 3/800-424-9300(CHEMTREC) CAGE:02QC3 === Contractor Identification === Company Name: UOP LLC Address:25 E ALGONQUIN RD Box:City:DES PLAINES State:IL ZIP:60017-5017 Country:US Phone:847-391-3189 FAX: 847-391-2953 CAGE:02QC3

Ingred Name:UNSATURATED DIMER FATTY ACID CAS:61788-89-4 Fraction by Wt: 40-70% Other REC Limits:NONE ESTABLISHED OSHA PEL:NONE ESTABLISHED ACGIH TLV:NONE ESTABLISHED

Ingred Name: AROMATIC SOLVENT

===========

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:REPEATED OR PROLONGED INHALATION OF SOLVENT VAPORS MAY CAUSE IRRITATION OF THE RESPIRATORY TRACT. INHALATION OF HIGH SOLVENT VAPOR CONCENTRATIONS MAY CAUSE DIZZINESS, HEADACHES, RESPIRATORY PROBLEMS O R CENTRAL NERVOUS SYSTEM DEPRESSION. SOLVENTS ARE KNOWN TO REMOVE THE NATURAL OILS

FROM THE SKIN. MAY CAUSE DERMATITIS. Effects of Overexposure:IRRITATING TO EYES & SKIN. PROLONGED SKIN EXPOSURE COULT RESULT IN DERMATITIS.

First Aid:SKIN: APLY A GENEROUS AMOUNT OF WATERLESS HAND CLEANER TO THE AFFECTED AREA. RUB BRISKLY ONTO THE SKIN, ON AND AROUND THE AFFECTED AREA. REMOVE THE MIXTURE OF CLEANER-ADDITIVE WITH PAPER TOWELS OR CLE AN, DRY RAGS; EYE: FLUSH WITH LARGE AMOUNTS OF WATER

FOR 15 MINUTES; INHALE: REMOVE TO FRESH AIR & GET MEDICAL ATTENTION; INGEST: DO NOT INDUCE VOMITING. GET MEDICAL ASSISTANCE.

Flash Point Method:PMCC Flash Point:>149F/65C Extinguishing Media:FOAM, CARBON DIOXIDE, DRY CHEMICAL. Fire Fighting Procedures:MAY PRODUCE IRRITATING OR POISONOUS GASES.

Spill Release Procedures: ISOLATE THE AFFECTED AREAS AND KEEP OUT ALL

UNAUTHORIZED PERSONNEL. CONFINE ENTRY TO THE CONTAMINATED AREA TO THOSE PERSONS WHO ARE PROPERLY PROTECTED. REMOVE SOURCES OF IGNITON. CLEAN UP CONTAMINATED SURFACE WITH A GENEROUS AMOUNT OF OIL ABSORBENT.

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED, PROPERLY LABELED CONTAINERS IN COOL, WELL-VENTILATED AREA AWAY FROM ALL IGNITION SOURCES. AVOID CONTACT WITH EYES/SKIN. Other Precau

tions:NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM(EVEN EMPTY) BECAUSE MATERIAL CAN IGNITE WXPLOSIVELY.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:WHERE NATURAL VENTILATION IS INADEQUATE, USE MECHANICAL VENTILATION, OTHER ENGINEERING CONTROLS OR A NIOSH-APPROVED SELF-CONTAINED BREATHING APPARATUS TO PREVENT INHALATION OF PRODUCT VAPORS. Ventilation:GOOD GENERAL MECHANICAL VENTILATION. Protective Gloves:RUBBER GLOVES. Eye Pro tection:CHEMICAL GOGGLES. Supplemental Safety and Health VAP-PRES:NIL.MFR SAYS"THE AROMATIC HYDROCARBON SOLVENT USED IN THIS PRODUCT HAS A BTX(BEZENE,TOLUENE,XYLENE)CONTENT OF