

ENMAR -- GRAY 16376;742-618 ENAMEL ALKYD GLOSS -- 8010-00-298-2298

=====
Product Identification
=====

Product ID:GRAY 16376;742-618 ENAMEL ALKYD GLOSS

MSDS Date:01/01/1985

FSC:8010

NIIN:00-298-2298

MSDS Number: BDWJX

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON IN

DUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 42.6%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexpo

sure:INH:ANESTHETIC, IRRIT OF RESP TRACT OR ACUTE
CNS DEPRSSN W/HDACHE,DIZ,UNCON,COMA. SKIN & EYE:IRRIT.

=====
First Aid Measures
=====

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTYOF WATER WHILE
REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR.
CALL A PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:85F TCC
Lower Limits:1.1
Extinguishing Media:SM FIRES:C
O*2, DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS.
Unusual Fire/Explosion Hazard:CLOSED CONTANERS EXPOSED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME, HOT
SURFACES, & ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID
BREATHING VAPORS. VENTILATE AREA.REMOVE W/INERT ABSORBENT &
NON-SPARING
TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LG QTY
IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ. DO NOT TAKE
INTERNALLY.ADD LABEL WARNING.
Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF
LIQ. IN EXCESS OF FEW IN.DO NOT FLAME CUT, BRAZE OR WELD COATED
MATERIAL W/O APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.
DOT:FLAM LIQUID.

=====
Exposure Cont
rols/Personal Protection
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR. CLSD:AIR-LINE
TYPE.
Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV
FUME
Protective Gloves:YES
Eye Protection:YES, FOR SPLASH
Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAMINATED
CLOTHING.
Supplemental Safety and Health
VAPOR PRESSURE:3.2;VAPOR DENSITY:HEAVIER THAN AIR;WT PER GALLON:9.1
LBS.

=====
Physical/Chemical Properties
=====

==

HCC:F3

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60.4

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER. DISPOSE IN ACCORDANCE W/FED.,STATE & LOCAL REGULATIONS.

Disclaim

er (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.