

HURON INDUSTRIES, INC. -- NEOLUBE NO 1 -- 9150-00-349-7443

=====
Product Identification
=====

Product ID:NEOLUBE NO 1
MSDS Date:01/01/1985
FSC:9150
NIIN:00-349-7443
MSDS Number: BDWYV
=== Responsible Party ===
Company Name:HURON INDUSTRIES, INC.
Address:2301 16TH STREET
Box:104
City:PORT HURON
State:MI
ZIP:48060-0104
Country:US
Info Phone Num:313-984-4213
Emergency Phone Num:313-984-4213
CAGE:034
32

=== Contractor Identification ===
Company Name:HURON INDUSTRIES INC
Address:2301 16TH ST
Box:610104
City:PORT HURON
State:MI
ZIP:48061-0104
Country:US
Phone:810-984-4213
CAGE:03432

=====
Composition/Information on Ingredients
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 93%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1%
OSHA P

EL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)
CAS:110-80-5
RTECS #:KK8050000
Fraction by Wt: 1%
OSHA PEL:S,200 PPM
ACGIH TLV:S, 5 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt: 1%
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9192

=====
Hazards Identification
=====

Effects of Overexposure:IRRITATION OF EYES
,NOSE AND THROAT.

=====
First Aid Measures
=====

First Aid:EYES:FLUSH W/WATER 15 MIN,CONSULT MD.SKIN:FLUSH
W/WATER.INHAL:REMOVE TO FRESH AIR.INGEST:INDUCE VOMITING,CALL DR.

=====
Fire Fighting Measures
=====

Flash Point:52F/11C (CC)
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. WIPE UP
SURPLUS AND CLEAN WITH ETHYL ALCOHOL AND/OR DETERGENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:AS FOR ISOPROPYL ALCOHOL. AVOID
IGNITION.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN
Ventilation:MECHANICAL
Protective Gloves:YES
Eye Protection:SPLASH PROOF GOGGLES
Supplemental Safety and Health
PKG 1 PT

=====

===== Physical/Chemical Properties =====

HCC:V3

Evaporation Rate & Reference:1.6 (BU ACE)

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DARK GRAY FLUID,ODOR OF ISOPROPANOL

Percent Volatiles by Volume:96

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZING AGENTS

===== Disposal Considerations =====

Waste Disposal Methods:AS PERMITTED BY LOCAL,STATE AND FED
REGS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular
situation.