

BEESTON, INC. -- DAMPING FLUID,SILICONE BASE; 5 CST -- 9150-00-435-2712

=====  
Product Identification  
=====

Product ID:DAMPING FLUID,SILICONE BASE; 5 CST

MSDS Date:01/01/1987

FSC:9150

NIIN:00-435-2712

MSDS Number: BDYVV

=== Responsible Party ===

Company Name:BEESTON, INC.

Box:1116

City:SCARBROUGH

State:ME

ZIP:04074

Country:US

Info Phone Num:207-883-5541

Emergency Phone Num:207-883-5541 CHEMTREC 80

0-424-9300

CAGE:LO373

=== Contractor Identification ===

Company Name:BEESTON

Address:540 DEERING AV

Box:1116

City:SCARBOROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:43728

Company Name:BEESTON, INC.

Box:1116

City:SCARBROUGH

State:ME

ZIP:04074

Country:US

Phone:207-883-5541

CAGE:LO373

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYDIMETHYLSILOXANE

CAS:63148-62-9

RTECS #:JT6484500

=====  
Hazards Identification  
=====

====

LD50 LC50 Mixture:ORAL RAT >5 GM/KG NEARLY NONTOXIC

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:TRANSITORY EYE IRRITATION IS THE MOST SERIOUS HUMAN EFFECT LISTED BY MANUFACTURER.

Effects of Overexposure:IRRITATION TO BODY TISSUES.

Medical Cond Aggravated by Exposure:NONE

=====  
===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER,GET MEDICAL ATTEN

TION. SKIN: WASH WITH

SOAP & WATER. INHALED: REMOVE TO FRESH AIR. INGESTED: GET MEDICAL ATTENTION.

=====  
===== Fire Fighting Measures =====

Flash Point Method:OC

Flash Point:>275F/134C

Extinguishing Media:DRY CHEMICAL,WATER SPRAY,FOAM,CARBON DIOXIDE.

Fire Fighting Procedures:WEAR SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:MAY EMIT IRRITATING OR TOXIC VAPORS.

=====  
===== Accidental Release Measures =====

Spill Rel

ease Procedures:WIPE UP OR ABSORB ON INERT MATERIAL. IF ON

FLOOR, USE SAWDUST, ETC., TO ELIMINATE SLIPPERY SURFACE.

Neutralizing Agent:NONE

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE TIGHTLY CLOSED IN A COOL,DRY AREA. SHELF LIFE IS 24 MO.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY REQUIRED.

Ventilation:NORMAL ROOM VENTILATION

Protective Gloves:RUBBER OR PLASTI

C IF DESIRED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE SPECIFIED

Work Hygienic Practices:NORMAL PERSONAL HYGIENE PRACTICES.

Supplemental Safety and Health

VISCOSITY PER SPEC: 5 CST MSDS COVERS PRODUCT PURCHASED ON CONTRACT  
DLA400-87-M-V598, DATED 26JUN87.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>572F/300C

Melt/Freeze Pt:M.P/F.P Text: