

EASTMAN KODAK COMPANY -- 140 4136,KODALITH RT LIQ DEVLPR REPL,PART A --
6750-00-457-1494

===== Product Identification =====

Product ID:140 4136,KODALITH RT LIQ DEVLPR REPL,PART A

MSDS Date:01/01/1985

FSC:6750

NIIN:00-457-1494

MSDS Number: BDZGY

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-72

2-5151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:HYDROQUINONE (SARA III)

CAS:123-31-9

RTECS #:MX3500000

Fraction by Wt: 5-10%

OSHA PEL:2 MG/M3

ACGIH TLV:2 MG/M3; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
Hazards Identification
=====

Effects of Overexposure:SKIN:MAY IRRITATE;REPREATED CONTACT MAY CAUSE ALLERGIC SKIN RX.

=====
First Aid Measures
=====

First Aid:SKIN:FLUSH SKIN IMMEDIATELY WITH PLENTY OF WATER

=====
Fire Fighting Measures
=====

Flash Point:NONE

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:DILUTE WITH COPIOUS AMOUNTS OF WATER.ABSORB WITH APPROPRIATE MATERIAL.PLACE IN APPROVED CONTAINER

=====
Handling and Storage
=====

Handling and Storage Precautions:NONE

Other Precautions:ROUTINE USE OF A NON-ALKALINE(ACID)TYPE HAND CLEANER WILL HELP MINIMIZE THE POSSIBILITY OF ALLERGIC SKIN RX.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NO

Ventilation:NO

Protect

ive Gloves:YES

Eye Protection:YES

Other Protective Equipment:AS NECESSARY TO PREVENT SKIN CONTACT

Supplemental Safety and Health

MSDS MAY BE REQD TO UPDATE HAZ INGRED FIELDS;HOWEVER THIS DATA DESCRIBES PART A HAVING PH APPROX 7.01;SEE NSN 6750004571495 FOR PART B DATA.

=====
Physical/Chemical Properties
=====

HCC:N1

Boiling Pt:B.P. Text:>212F

Vapor Pres:17

Vapor Density:0.6

Spec Gravity:1.29

Solubility in Water:COMPLETE

Appearance and Odor:SLIGHT YELLOW,ODO

RLESS
Percent Volatiles by Volume:55

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
MINERAL ACIDS
Hazardous Decomposition Products:SULFUR DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR LANDFILL OBSERVE FEDERAL,LOCAL, &
STATE DISPOSAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by
elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.