

DEFT CHEMICAL COATINGS -- 03-W-46 CATALYST,WHITE 37875,POLYURETHANE --
8010-00-482-5667

===== Product Identification =====

Product ID:03-W-46 CATALYST,WHITE 37875,POLYURETHANE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-482-5667

Kit Part:Y

MSDS Number: BDZZQ

=== Responsible Party ===

Company Name:DEFT CHEMICAL COATINGS

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92714-6205

Country:US

CAGE:EO4

18

=== Contractor Identification ===

Company Name:DEFT CHEMICAL COATINGS

CAGE:EO418

Company Name:DEFT, INC.

Address:17451 VON KARMAN AVE

City:IRVINE

State:CA

ZIP:92614

Country:US

Phone:949-474-0400

CAGE:33461

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10.0%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingr

ed Name:METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 11.5%

OSHA PEL:100 PPM/75 STEL

ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5.0%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS:111-15-9

RTECS #:KK8225000

Fraction

by Wt: 11.0%

OSHA PEL:S,100 PPM

ACGIH TLV:S, 5 PPM; 9192

Ingred Name:1,6-DIISOCYANATOHEXANE (HEXAMETHYLENE DIISOCYANATE)

CAS:822-06-0

RTECS #:MO1740000

Fraction by Wt: 0.5%

ACGIH TLV:0.005 PPM; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====
===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN IRRITANT,INHALTION CAN IRRITATE LUNGS
OR CAUSE NARCOSIS.

=====
===== First Aid Measures =====

First Aid:FOR SKIN: WAS WITH

SOAP&WATER. EYES: FLUSH WITH WATER AND
CALL PHYSICIAN. FOR INHALATION REMOVE TO FRESH AIR

=====
Fire Fighting Measures
=====

Flash Point:28F=-2.2C

Lower Limits:1.60

Extinguishing Media:CARBON DIOXIDE, FOAM OR DRY CHEMICALS

Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:DO NOT APPLY TO HOT SURFACES OF WHERE
OPEN FLAME OR SPARKS ARE PRESET

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB WITH OIL-ABSORBING COMPOUND OR DRY
RAGS. FLUSH WITH LARGE VOLUME OF WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP IN TIGHTLY SHUT CONTAINERS WITH
ADEQUATE VENTILATION

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:CARTRIDGE TYPE RESPIRATOR WITH PARTICULATE
FILTERS MSC CAT CR84306

Ventilation:EXHAUST FAN

Protective Gloves:YES

Eye Protecti

on:YES

Supplemental Safety and Health

TWO PAGES ONE AND TWO ARE INCLUDED. ONE FOR EACH QUART OF DIFFERENT
MATERIAL. HANDLING DATA IS THE SAME. KEY1:F3.

=====
Physical/Chemical Properties
=====

HCC:F3

Boiling Pt:B.P. Text:175F=79.4C

Vapor Pres:040

Vapor Density:>AIR

Spec Gravity:0.9120

Evaporation Rate & Reference: