

CHEMRAY COATINGS CORPORATION -- TT-P-1757,COMP L, COLOR Y -- 8010-00-515-2208
===== Product Identification =====

Product ID:TT-P-1757,COMP L, COLOR Y
MSDS Date:01/01/1987
FSC:8010
NIIN:00-515-2208
MSDS Number: BFCBX
=== Responsible Party ===
Company Name:CHEMRAY COATINGS CORPORATION
Address:209 MICHIGAN AVE.
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Emergency Phone Num:201-245-1111
CAGE:OBRN9

=== Contractor Identification ===
Company Name:CHEMRAY COATING CORP
Address:209 N MICHIGAN AVE
Box:City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:201-245-1111
CAGE:33832
Company Name:CHEMRAY COATINGS CORP.
Address:209 N. MICHIGAN AVE.
Box:NA
City:KENILWORTH
State:NJ
ZIP:07033
Country:US
Phone:800-924-9300
CAGE:OBRN9

===== Composition/Information on Ingredients =====

Ingred Name:ZINC CHROMATE
CAS:13530-65-9
RTECS #:GB3290000
Fraction by Wt: 11.9%
OSHA PEL:0.1 MG/M3 (CRO3)

)
ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 5.1%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 22.3%
OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5.0%
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 92
93
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1.3%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:EXCESSIVE INHALATION MAY CAUSE
HEADACHE,DIZZ,UNCONSC,COMA.SKIN/EYE CONTACT:PRIMARY IRRIT,DRY SKIN.

=====
===== First Aid Measures =====

First A

id:INHALATN:REMOVE FROM EXPOSURE,RESTORE BREATHNG.KEEP WARM.CALL MD.EYES:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN.CALL MD.
SKIN:REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA W/SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:100F(38C) PMCC
Lower Limits:0.7
Upper Limits:6
Extinguishing Media:CO*2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:COOL CLOSED CONTAINERS W/WATER FOG.SELF-CNTND BREATHNG APP
Unusual Fire/Explosion Hazard:CL
USED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE W/ABSORBENT MATERIAL OR FLUSH W/WATER INTO RETAINING AREA OR CONTAINER.AVOID SPARKS,FIRE & HOT SURFACES.VENTILATE AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP FROM HEAT,SPARKS,OR OPEN FLAME.USE W/ADEQUATE VENTILATION.AVOID PROLONGED OR REPEATED CONTACT W/SKIN.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATORY PROTECTN FOR EXPOSURE OF CONCERN
Ventilation:LOCAL-KEEP BELOW TLV&LEL.MECH-EXPLOSION PROOF
Protective Gloves:YES
Eye Protection:GOGGLES
Other Protective Equipment:IMPERMEABLE APRON FOR PROLONGED OR REPEATED CONTACT.
Supplemental Safety and Health
PRODUCT ALSO CONTAINS 27% ALKYD RESIN,