

AMERON INDUSTRIAL COATINGS DIVISION -- CLEAR -- 8010-00-527-1507

=====
Product Identification
=====

Product ID: CLEAR
MSDS Date: 01/01/1987
FSC: 8010
NIIN: 00-527-1507

MSDS Number: BFCQH
=== Responsible Party ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION
Emergency Phone Num: 316-733-1361
CAGE: 09869

=== Contractor Identification ===

Company Name: AMERON INDUSTRIAL COATINGS DIVISION
Address: 201 N
BERRY ST
Box: City: BREAS
State: CA
ZIP: 92621-3904
Country: US
Phone: 714-529-4597
CAGE: 09869

=====
Composition/Information on Ingredients
=====

Ingred Name: CYCLOHEXANONE (SARA III)
CAS: 108-94-1
RTECS #: GW1050000
Fraction by Wt: 7.0%
OSHA PEL: S, 50 PPM
ACGIH TLV: S, 25 PPM; 9293
EPA Rpt Qty: 5000 LBS
DOT Rpt Qty: 5000 LBS

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS: 78-93-3
RTECS #: EL6475000
Fraction by Wt: 7.0%
OSHA PEL: 200 PPM/300 STEL
ACGIH TLV: 200 PPM/300ST

EL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 7.0%
OSHA PEL:100 PPM

Ingred Name:ISOBUTYL ACETATE (SARA III)
CAS:110-19-0
RTECS #:AI4025000
Fraction by Wt: 7.0%
OSHA PEL:150 PPM
ACGIH TLV:150 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 16.0%
OSHA PEL:150 PPM/200 STEL
ACGIH TLV:150 PPM/200STEL;9192
E
PA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A
PHYSICIAN IF CONDITIONS PERSIST.

=====

= Fire Fighting Measures =====

Flash Point:28F TCC

Lower Limits:1.1

Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LAGE
FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY
EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. REMOVE WITH INERT ABSORBEN
T AND NON-SPARKING
TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE
FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR O
R AIR
SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

NT8050000 ISOPROPYL ALCOHOL LESS THAN 5 PERCENT. RESPIRATOR USE BASED
ON CHEM CONC. AND CONDITION OF USE

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:118-321F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:90.0

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

Stability Condition to Avoid: AVOID FIRE, HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.