

ANDREW BROWN -- ACRYLIC NC L-698 13538 ORANGE-YELLOW -- 8010-00-527-2518

=====  
Product Identification  
=====

Product ID:ACRYLIC NC L-698 13538 ORANGE-YELLOW

MSDS Date:01/01/1985

FSC:8010

NIIN:00-527-2518

MSDS Number: BFCVC

=== Responsible Party ===

Company Name:ANDREW BROWN

Address:5431 DISTRICT BLVD

City:VERNON

State:CA

ZIP:90040

Country:US

CAGE:LO521

=== Contractor Identification ===

Company Nam

e:ANDREW BROWN

Address:5431 DISTRICT BLVD

Box:City:VERNON

State:CA

ZIP:90040

Country:US

CAGE:LO521

Company Name:KOPPERS CO INC

Address:5431 DISTRICT BLVD

Box:City:VERNON

State:CA

ZIP:90040

Country:US

CAGE:71191

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 23%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300STEL;9394

EPA Rpt Qty:5000 LBS

DO

T Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 17%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM/75 STEL; 9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 26%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:HEADACHE, NAUSEA, NOSE BLEEDS

=====  
First Aid Measures  
=====

First Aid:REMOVE VICTIMS FROM VAPOR AREA. REMOVE BREATHING IF NECESSARY  
REMOVE CLOTHES THAT HAS BEEN AFFECTED BY VAPORS. WASH W/SOAP &  
WATER: FLUSH EYES W/WATER

=====  
Fire Fighting Measures  
=====

Flash Point:26 F/-3 C

Lower Limits:1.3

Extinguishing Media:CARBON DIOXIDE FOAM OR DRY CHEMICAL

Fire Fighting

Procedures:DO NOT USE WATER.

Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIVE MIXTURE BETWEEN  
UPPER & LOWER LIMITS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:ADEQUATE VENTILATION, APPLY ABSORBENT MATERIAL

=====  
Handling and Storage  
=====

Handling and Storage Precautions:FLAMMABLE: STORE AWAY FROM OPEN FLAME  
& HIGH HEAT.

Other Precautions:DO NOT TAKE INTERNALLY, AVOID PROLONGED CONTACT

W/SKIN

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:FOR CONFINED AREAS,USE BUR.OF MINES APPRVD  
RESPIR DEVICE APRVL 23B13

Ventilation:SHOULD BE ADEQ TO KEEP LOWR LEVELS BELOW L.E.L.

Protective Gloves:RUBBER GLOVES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:RUBBER SOLES MUST BE WORN (NO STATIC  
ELECTRICITY)

Supplemental Safety and Health

=====  
===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P

. Text:176-232 F

Vapor Density:HEAV

Percent Volatiles by Volume:90

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:KEEP PRODUCT AWAY FROM OPEN FLAME.

Hazardous Decomposition Products:CH\*4,N, NO\*2, CO,CO\*2 WHEN COMBUSTED

=====  
===== Disposal Considerations =====

Waste Disposal Methods:PUT IN METAL CONTAINER & SEAL FOR DISPOSAL

Disclaimer (provided with this information by th  
e compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.