

EASTMAN KODAK COMPANY, (PHIPPS PRODUCTS) -- TT-I-735,ISOPROPYL ALCOHOL,TECHNICAL
-- 6810-00-543-7915

===== Product Identification =====

Product ID:TT-I-735,ISOPROPYL ALCOHOL,TECHNICAL

MSDS Date:01/01/1985

FSC:6810

NIIN:00-543-7915

MSDS Number: BFDRZ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY, (PHIPPS PRODUCTS)

Address:186 LINCOLN ST SUITE 502

City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Emergency Phone Num:800-426-4333

CAGE:5K871

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

Company Name:PHIPPS PRODUCTS CORP

Address:186 LINCOLN ST SUITE 502

Box:City:BOSTON

State:MA

ZIP:02111-2403

Country:US

Phone:OUT OF BUSINESS

CAGE:86511

===== Composition/Information on Ingredients =====

Ingred Name:ISOPROP

YL ALCOHOL (SARA III)
CAS:67-63-0
RTECS #:NT8050000
Fraction by Wt: 100%
OSHA PEL:400 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9192

===== Hazards Identification =====

Effects of Overexposure:NARCOTIC EFFECT INDUCED BY HIGH
CONCENTRATIONS,IRRITATION OF SKIN,IRRITATION OF RESPIRATORY TRACT

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES:FLUSH W
LG AMTS H*2O FOR 15 MIN;S
KIN:FLUSH W LG AMTS H*2O;INGEST:RINSE
MOUTH,STOMACH WASH,FOLLOWED BY SALINE CATHARSIS. GET MEDICAL
ATTENTION.

===== Fire Fighting Measures =====

Flash Point:65F,18.3C TOC
Lower Limits:2.3
Upper Limits:12.8
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,CARBON DIOXIDE
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;H*2O SPRAY COOL
CONT.
Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IN HEAT OF FIRE.

===== Accidental Release Mea
sures =====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS. ELIM IGNITION
SOURCES. STOP LEAK. H*2O SPRAY COOL CONT/DIVERT SPILL FROM
FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL
ABSORBENT,SHOVEL INTO METAL DRUMS;LG SPILL:DI KE W COMMERCIAL
ABSORBENT,PUMP INTO COVERED DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW
FIRE RISK AREA. PROTECT FROM PHYSIC

AL DAMAGE. AVOID ANY PHYSICAL CONTACT.KEEP CONTAINERS TIGHTLY CLOSED.
Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL.
REMOVE & WASH CONTAMINATED CLOTHING. MAINTAIN STRICT HYGIENE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:AIR LINE RESPIRATOR/ORGANIC CANISTER IF VAPORS PRESENT.

Ventilation:LOCAL EXHAUST TO CNTROL TLV IN AIR

Protective Gloves:RUBBER

Eye Protection:SAFETY/CHEM GOGGLES

Other Protective Equipment:FACE SH

IELD,COVERALLS & GAS MASK WHEN USING.

Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2

Boiling Pt:B.P. Text:180F,82.2C

Vapor Pres:33

Vapor Density:2.07

Spec Gravity:0.780

Evaporation Rate & Reference:1.7,BUTYL ACETATE

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,CHARACTERISTIC

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

Sta

bility Condition to Avoid:IGNITION SOURCES

=====
Disposal Considerations
=====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS. MFG SUGGESTS INCINERATION, OR FLUSH INTO CONTAINERS & S HIP TO APPROVED DISPOSAL AREA.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by

elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.