Product ID:ELECTRIC CONTACT, CLEANG & LUBRICATING CMPD MSDS Date:01/01/1987 FSC:6850 NIIN:00-570-9360 **MSDS Number: BFFPV** === Responsible Party === Company Name: CHEMTRONICS, INC Address:681 OLD WILLETS PATH City:HAUPPAUGE State:NY ZIP:11787 Country:US Info Phone Num:800-645-5244 Eme rgency Phone Num:800-645-5244 CAGE:LO604 === Contractor Identification === **Company Name: CHEMTRONICS INC** Address:8125 COBB CENTER DRIVE Box:City:KENNESAW State:GA ZIP:30152 Country:US Phone:770-424-4888/800-645-5244 CAGE:21267 Company Name: CHEMTRONICS, INC Address:681 OLD WILLETS PATH Box:City:HAUPPAUGE State:NY ZIP:11787 Country:US Phone:800-645-5244 CAGE:LO604

Ingred Name: METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6
RTECS #:KJ2975000
Fraction by Wt: 66.0%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III) CAS:75-71-8 RTECS #:PA8200000 Fraction by Wt: 32.0% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS Ozone Depleting Chemical:1

Ingred Name:POLY(ETHYL)SILOXANE CAS:9016-00-6 RTECS #:TQ2690000 Fraction by Wt: 2.0 % ACGIH TLV:NOT SPECIFIED

Effects of Overexposure:LIGHT-HEADNESS,GIGINESS,NARC,CARDIAC ARRYTHMIAS.AT HIGH CONCENTRATIONS,IF INHALED,CAN CAUSE DEATH.

First Aid:SKIN:WASH W.SOAP & H*20. EYES:FLUSH W. H*20. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER G IVE

ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

Flash Point:N/A(SEE SUP DAT) Extinguishing Media:WATER FOG Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP Unusual Fire/Explosion Hazard:CONTAINERS MAY RUPTURE IN HEAT OF FIRE.TOXIC GAS MAY EXCAPE DURING FIRE.

Spill Release Procedures: VENTILATE AREA-ESPECIALLY LOW PLACES WHERE HEAVY VAPOR MIGHT CO LLECT.REMOVE IGNITION SOURCES.KEEP OUT OF WATER SUPPLIES.ABSORB AND WIPE UP SMALL SPILLS.TRANSFER TO CLOSED METAL CONTAINERS.LG SPILL:DIK E WITH COMMERCIAL OR OTHER ABSORBENT,DISPOSE LATER

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED,LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STRICT HYGIENE FOR CHEM HANDLING. Other Precautions:NONE

Respiratory Protection:USE AIR MASKS IN HIGH CONCENTRATIONS. Ventilation:LG AMTS RELEASED-LOCAL EXHAUST,MECHANICAL IN LOW AREAS. Protective Gloves:IMPERVIOUS Eye Protection:CHEM SPLASH GOGGLES Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Supplemental Safety and Health

BP RANGE:-6C-149C.VAP PRESS:DICHLORODIFLUOROETHANE-4893MM.FP FOR POLYSILOXANE G1:500F TOC.

======= Physical/Chem

ical Properties ===============

HCC:V2 Boiling Pt:B.P. Text:-21F-300F Vapor Pres:SUP Vapor Density:6.33 Spec Gravity:1.3 Evaporation Rate & amp; Reference:>1(REF UNKNOWN) Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS-SLIGHT ETHEREAL ODOR. Percent Volatiles by Volume:96

Stability Indicator/Materials to Avoid:YES IN WATER-SLOW HYDROLYSIS TO CORR ACID,ALUMINUM & ITS ALLOYS. Stability Condition to Avoid:OPEN FLA

MES,HIGH TEMPERATURES,WELDING ARCS.

Hazardous Decomposition Products:HCL,HF,POSS CARBONYL FLUORIDES,SM AMTS PHOSGENE,FLUOR,CHLOR.

Waste Disposal Methods:RECLAIM BY DISTILATION.SEND TO LICENSED RECLAIMER OR DISPOSAL CONTRACTOR.COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Departm ent

of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.