

View NSN Online: <https://aerobasegroup.co.il/nsn/6850-00-570-9360>

W.M. BARR & CO -- CLEANING & LUBRICATING CPD,ELECTRIC CONTACT -- 6850-00-570-9360

=====
Product Identification
=====

Product ID:CLEANING & LUBRICATING CPD,ELECTRIC CONTACT

MSDS Date:01/01/1985

FSC:6850

NIIN:00-570-9360

MSDS Number: BFFPY

=== Responsible Party ===

Company Name:W.M. BARR & CO

Emergency Phone Num:901-775-0100

CAGE:IO929

=== Contractor Identification ===

Company Name:W.M. BARR & CO

Address:2105 CHANNEL AVE

Box:1879

City:MEMPHIS

State:TN

ZIP:38101

Country:US

Phone:901-775-0100

CAGE:IO929

Company Name:W.M. BARR & COMPANY/KLEAN-STRI, DIVISION OF

Address:2105 CHANNEL AVENUE

Box:1879

City:MEMPHIS

State:TN

ZIP:38101

Country:US

Phone:901-775-0100

CAGE:91522

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 63.5%

Other REC Limits:NONE RECOMMENDED

OS

HA PEL:350 PPM
ACGIH TLV:350 PPM/450STEL;9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS
Ozone Depleting Chemical:1

Ingred Name:SILICONE FLUID
RTECS #:VW1620000
Fraction by Wt: 2.5%

Ingred Name:DICHLORODIFLUOROMETHANE (SARA III)
CAS:75-71-8
RTECS #:PA8200000
Fraction by Wt: 34%
OSHA PEL:1000 PPM
ACGIH TLV:1000 PPM; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS
Ozone Depleting Chemical:1

=====
Hazards Identification
=====

Effects of Overexposure:DIZYNES,DROW
, AND UNCONSCIOUSNESS IN INEREASING
CONCENTRATIONS.CONTACT DEFATS SKIN.

=====
First Aid Measures
=====

First Aid:REMOVE TO FRESH AIR.CALL A PHYSICIAN.DO NOT GIVE EPINEPHRINE
OR SIMILAR DRUGS.SKIN/EYES:FLUSH WITH WATER.GET MEDICAL
ATTENTION.IF SWALLOWED.GET MEDICAL ATTENTION OR CALL YOUR POISON
CONTROL CENTER.

=====
Fire Fighting Measures
=====

Lower Limits:6.3
Upper Limits:UNK
Extinguishing Media:EXTINQUI
SH W. AGENT SUITABLE FOR SURROUNDING FIRE.
Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP
Unusual Fire/Explosion Hazard:CONTENTS UNDER PRESS.MAY RUPTURE IN HEAT
OF FIRE.TOXIC DECOMP PRODUCTS MAY BE FORMED IN HEATOF FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:STOP LEAK. NO IGNITION SOURCES IN HAZ AREA.
ISOLATE AREA UNTIL GAS DISPERSED.USE H*2O SPRAY TO REDUCE
BVAPORS.KEEP UPWIND. SM SPILL:ABSORB W SAND, EARTH,OTHER ABSORB

HALIDE(PHOSGENE).

===== Disposal Considerations =====

Waste Disposal Methods:EVAPORATION IS FAIRLY RAPID.USE ABSORPTIVE MEDIA FOR LARGE AMOUNTS.DISPOSE IAW APPLICABLE LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.