View NSN Online: https://aerobasegroup.co.il/nsn/8010-00-598-7212 PRATT AND LAMBERT-WICHITA DIV -- FIRE RED 12199 -- 8010-00-598-7212 Product ID:FIRE RED 12199 MSDS Date:01/01/1985 FSC:8010 NIIN:00-598-7212 MSDS Number: BFHMS === Responsible Party === Company Name: PRATT AND LAMBERT-WICHITA DIV Address:945 BURLINGTON Box:206 City: KANSAS CITY State:MO ZIP:64141 Country:US CAGE:92216 === Contractor Identification === Company Na me:PRATT AND LAMBERT INC Address:945 BURLINGTON Box:206 City: KANSAS CITY State:MO ZIP:64141 Country:US CAGE:92216

======= Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 40-5% OSHA PEL:100 PPM

========== Hazards Identification ===============

Effects of Overexposure: INHALATION: ANESTHETIC, IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYS DEPRESS ION CHAR

ACTER
======================================
First Aid:IN CASE OF CONTACT, FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOVE TO FRESH AIR. CALL A MD. IF SYMPTOMS PERSIST.
======================================
Flash Point:104F Lower Limits:1.10 Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOC.(NFPA)CLASS B EXTINGUISHE Fire Fighting Procedures:SELF-CONTAINED BREATHING APPA
RATUS SHOULD BE AVAIL FOR FIREM Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS AND OPEN FLAME.CLOSED
========= Accidental Release Measures ==========
Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,AND ELECTRICAL,STATIC OR FRICTIONAL SPARKS)AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.
======================================
Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.  Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL.
====== Exposure Controls/Personal Protection ========
Respiratory Protection: IN OUTDOOR OR OPEN AREAS, USE BUREAU OF MINES APPROVED MECHANICAL FIL

Protective Gloves: REQUIRED FOR PR

Eye Protection: USE SAFETY EYEWARE DESIGN

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAIL FOR FIREMEN.WATER SPRAY MAY BE INEFFECTIVE, WATER MAY BE USED TO COOL CLOSED CONTAINERS TO PREVENT PRESSURE BUILD-UP AND POSSIBLE AUTOIGNITION

HCC:F4
Boiling Pt:B.P. Text:311 T
O 373F
Vapor Pres:3.2
Percent Volatiles by Volume:64

========= Stability and Reactivity Data ===========

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES,HEAT,AND HOT SURFACES.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS. INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.