

HARSHAW/FILTROL PARTNERSHIP -- FILTROL CLAY PRODUCT DISICCITE 25 -- 6850-00-619-7804

=====
Product Identification
=====

Product ID:FILTROL CLAY PRODUCT DISICCITE 25

MSDS Date:01/01/1987

FSC:6850

NIIN:00-619-7804

MSDS Number: BFJJF

=== Responsible Party ===

Company Name:HARSHAW/FILTROL PARTNERSHIP

Emergency Phone Num:216-292-9200

CAGE:8Z371

=== Contractor Identification ===

Company Name:HARSHAW/FI

LTRON PARTNERSHIP

Address:30100 CHAGRIN BLVD

Box:City:CLEVELAND

State:OH

ZIP:44124-5705

Country:US

Phone:216-349-7300

CAGE:8Z371

=====
Composition/Information on Ingredients
=====

Ingred Name:SILICA, CRYSTALLINE - QUARTZ

CAS:14808-60-7

RTECS #:VV7330000

Fraction by Wt: 3.0%

OSHA PEL:SEE TABLE Z3

ACGIH TLV:0.1 MG/M3 RDUST;9293

=====
Hazards Identification
=====

Effects of Overexposure:EYES&SKIN:IRRITATION ON PROLONGED

CONTACT;INHAL:IRRIT

,PULMONARY FIBROSIS,COUGH,DYSPNEA,WHEEZING

=====
First Aid Measures
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H*20 FOR 15 MIN;INGEST:RINSE MOUTH;

GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER

SYMPTOMS OF OVEREXPOSURE.

=====
Fire Fighting Measures
=====

Extinguishing Media:USE ANY MEDIA FOR SURROUNDING FIRES.

Fire Fighting Procedures:USE NIOSH/M

SHA APPROVED SCBA IN AN ENCLOSED
AREA.

Unusual Fire/Explosion Hazard:NONE NOTED BY MFR.

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION:SCOOP OR VACUUM
INTO CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL AND DRY AREA.KEEP
CONTAINER TIGHTLY CLOSED.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES;DO NOT INHALE
VAPORS.

===== Exposure Controls/Personal Protection =====

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN