

EASTMAN KODAK CO. -- 146 4080 KODAKFIX(OLD FORMULATION) -- 6750-00-619-9943

===== Product Identification =====

Product ID:146 4080 KODAKFIX(OLD FORMULATION)

MSDS Date:12/12/1986

FSC:6750

NIIN:00-619-9943

MSDS Number: BFJJM

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE ST.

City:ROCHESTER

State:NY

ZIP:14650

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Id

entification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction by Wt: 30-40%

Other REC Limits:NONE ESTABLISHED

Ingred Name:SODIUM METABISULFITE

CAS:7681-57-4

RTECS #:UX8225000

Fraction by Wt: 5-15%

OSHA PEL:5 MG/M3

ACGIH

TLV:5 MG/M3; 9192

Ingred Name:SODIUM ACETATE
CAS:126-96-5
RTECS #:AJ4375000
Fraction by Wt: 5-10%
Other REC Limits:NONE ESTABLISHED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 55-65%

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEE "OVEREXPOSURE SYMPTOM"
E
ffects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO
HEALTH.

===== First Aid Measures =====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:WEAR SCBA & PROTECTV CLOTHG TO P
REVENT
SKIN/EYE CONTACT.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE
PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENTS. STOP
LEAK W/O RISK. DIKE LIQUID W/ABSORBENT & TRANSFER LIQ TO SALVAGE
TANK. MFR SUGGESTS TO FLUSH MATERIAL TO AN ACID-FREE SEWER WITH
LARGE AMOUNTS OF WATER.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP
CONTAINERS TIGHTLY CLOSED
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED
Ventilation:MECHANICAL (GENERAL)
Protective Gloves:AS REQUIRED
Eye Protection:SAFETY GLASSES
Other Protective Equipment:NONE SHOULD BE NEEDED,BUT GOOD HYGIENE
PRACTICE BE
FOLLOWED
Supplemental Safety and Health
THIS PRODUCT HAS A KODAK'S SOLUTION NUMBER 4247. THIS IS AN OLD
FORMULATION. THE NEW FORMULATION CAN BE FOUND UNDER P/N IND:B, AND
IT HAS A KODAK SOLUTION NUMBER 5385.

===== Physical/Chemical Properties =====

HCC:N1
Boiling Pt:B.P. Text:>212F/>100C
Vapor Pres:18
Vapor Density:0.6
Spec Gravity:1.28
Solubility in Water:COMPLETE
Appearance and Odor:COLORLESS SOLUTION,AMMONIA ODOR
Percent Volatiles by Volume:55

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:EXCESSIVE HEAT
Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL EMIT OXIDES
OF SULFUR & NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:MANUFACTURER STATES THAT DISCHARGE, TREATMENT OR
DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by

the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.