

THE AKRON PAINT & VARNISH CO. -- LR-7126B BLACK W W TYPE II #37038 -- 5610-00-641-0427
===== Product Identification =====

Product ID:LR-7126B BLACK W W TYPE II #37038

MSDS Date:01/01/1987

FSC:5610

NIIN:00-641-0427

MSDS Number: BFJSF

=== Responsible Party ===

Company Name:THE AKRON PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

CAGE:KO225

=== Contr

actor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

Company Name:THE AKRON PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

Box:City:AKRON

State:OH

ZIP:44301-1624

Country:US

CAGE:KO225

===== Composition/Information on Ingredients =====

Ingred Name:N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000

Other REC Limits:NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/200STEL;9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 44.2%

OSHA PEL:100 PPM

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Ingred Name:BUTYL CELLOSOLVE

RTECS #:EP3600000

Ingred Name:BUTYRALDEHYDE OXIME

CAS:110-69-0

RTECS #:ES3500000

Fraction by Wt: 0.5%

=====
===== Hazards Identification =====

Effects of Overexposure:PROLONGED OR R

EPEATED EXPOSURE MAY CAUSE

NAUSEA,HEADACHE & LOSS OF CONSCIOUSNESS;NARCOSSIS & IRRITAT

=====
===== First Aid Measures =====

First Aid:SKIN CONTACT:WASH CAREFULLY W/MINERAL SPIRITS,THEN W/SOAP &
WATER. EYE CONTACT:FLUSH PROMPTLY & THOROUGHLY W/WATER &"OBTAIN
MEDICAL ATTENTION."INHALATION:REMOVE INDIVID. TO FRESH AIR AND USE
OXYGEN IF NECESSARY.OBTAIN MEDICAL ATTENTION."

=====
===== Fire Fighting Measures =====

Flash
Point:50F CC VM&P 10
Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEMICAL.
Fire Fighting Procedures:WATER SPRAY TO COOL CONTAINERS.WEAR
SELF-CONTAINED BREATHING
Unusual Fire/Explosion Hazard:HEAT MAY CAUSE DISRUPTIVE PRESSURE OF
CONTAINERS,& FLAMMABLE VAPORS MAY FORM EXPLOSIVE MIXTURE W/AIR

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. DAM-UP TO
LIMIT SPREADING. ABSORB ON INERT MATERIAL.VENTILATE AREA

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT DROP CONTAINERS.AVOID HEAT,
SPRAKS & OPEN FLAME.

Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED INHALATION &
BODY CONTACT.GROUND CONTAINER WHILE POURING. CONSULT NFPA CODE.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE APPRO. BUREAU OF MINES APPROVED RESPIRATOR
WHEN SPRAYING OR APPL

Ventilation:PROVIDE ADEQUATE VEN
TILATION & EXPLOSION-PROOF EQUIPMENT.

Protective Gloves:CHEMICAL RESIST

Eye Protection:SAFETY GOGGLES W/SIDE SHI

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

BOILING RANGE-I.B.P.:240F 115C(VM&P)

=====
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:I.B.P:240F

Vapor Density:HEAV

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:67.7

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID OXIDIZING AGENTS

Hazardous Decomposition Products:COMBUSTION IN RESTRICTED ENVIRONMENT
CAN PRODUCE CARBON MONO

Conditions to Avoid Polymerization:STORAGE OF WATTED COMBUSTIBLE
MATERIALS MAY CAUSE SPONTANEOU

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/APPLICABLE POLLUTION
CONTROL REGULATIONS.

Disclaimer (provided with this information by the co

mpiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.