

ENMAR -- 726-001; PRIMER COATING GRAY 36440 -- 8010-00-664-6302

=====
Product Identification
=====

Product ID:726-001; PRIMER COATING GRAY 36440

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-6302

MSDS Number: BFJVV

=== Responsible Party ===

Company Name:ENMAR

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

CAGE:OO111

=== Contractor Identification ===

Company Name:AMERON INDUSTRI

AL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

Company Name:ENMAR

Address:201 N BERRY ST

Box:City:BREA

Phone:(316)-7333-1361

CAGE:OO111

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INH:ANESTHETIC,IRRIT OF

RESP TRACT OR ACUTE CNS
DEPRESSN W/ HDACEH,DIZZY,UNCON,COMA.SKIN/EYE IRRITAT

=====
First Aid Measures
=====

First Aid:SKIN/EYES:FLUSH WITH WATER. REMOVE CONTAMINATED
CLOTHING.INHAL:MOVE TO FRESH AIR. CALL DR.IF NEEDED.

=====
Fire Fighting Measures
=====

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES:CO*2, DRY CHEM. LG FIRES:POLYMER FOAM
PREFERRED

Fire Fighting Procedures:USE SELF-CONTANED
BREATHING APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPLODED TO HEAT MAY
EXPLODE DUE TO PRESSURE BUILD-UP.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME,HOT
SURFACES,& ELECTRICAL,STATIC,OR FRICTIONAL SPARKS).AVOID BREATHING
VAPORS.VENTILATE AREA.REMOVE W/INERT ABSORBENT & NON-SPARKING
TOOLS.

=====
Handling and Storage
=====

Handling and Stor

age Precautions:DO NOT STORE ABOVE 120F STORE LG QTY
IN BLDG DESIGNED TO STORE NFPA CLASS ONE FLAM LIQ DO NOT TAKE
INTERNALLY. ADD LABEL WARNING.

Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL IN
EXCESS OF FEW INCHES. DO NOT FLAME CUT,BRAZE OR WELD COATED
MATERIAL W/O APPROVED RESPIRATOR OR VENTILATION.DOT:FLAM LIQUID.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:RESTRICT VENT:CHEM-MECH FLTR.CLSD:AIR-LINE TYPE
Vent

ilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LE BELOW LIMIT, REMV FUME
Protective Gloves:YES
Eye Protection:YES, FOR SPLASH
Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING
Supplemental Safety and Health
THIS PRODUCT IS A SYNTHETIC SURFACER. VAPOR PRESSURE: 3.2 ; VAPOR
DENSITY: HEAVIER THAN AIR; WEIGHT: 10.11 LBS PER GALLON.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Pres:3.2
Evaporation Rate & Reference
:SLOWER THAN ETHER
Solubility in Water:>1
Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINER.DISPOSE IN
ACCORDANCE W/FED.,STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling
agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.