View NSN Online: https://aerobasegroup.co.il/nsn/5970-00-647-3676

PRODUCTS TECHNIQUES INC -- PT-107 -- 5970-00-647-3676

============ Product Identification ==============

Product ID:PT-107

MSDS Date:01/01/1985

FSC:5970

NIIN:00-647-3676

MSDS Number: BFJWS === Responsible Party ===

Company Name: PRODUCTS TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

City:RIALTO State:CA ZIP:92316 Country:US

**Emergency Phone Num:NONE** 

CAGE:IO636

=== Contractor Identification ===

Company Name:PRODUCT

S TECHNIQUES INC

Address:3271 SO RIVERSIDE AVE

Box:City:RIALTO

State:CA ZIP:92316 Country:US

Phone:714-887-3951;213-770-3600

CAGE:10636

Company Name: PRODUCTS/TECHNIQUES INC

Address:3271 S RIVERSIDE AVE

Box:City:RIALTO

State:CA ZIP:92376 Country:US

Phone:909-877-3951

CAGE:06341

====== Composition/Information on Ingredients ========

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 41.6% OSHA PEL:100 PPM

Ingred Name: XYLENES (O-,M-,P-

ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 3.62% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:RESIN Fraction by Wt: 51.3%
Ingred Name:SALICYLANILIDE CAS:87-17-2 RTECS #:VN7850000 Fraction by Wt: 3.45% ACGIH TLV:500 PPM
========= Hazards Identification ===========
Effects of Overexposure:HEADACHE,NAUSEA,MODERATELY IRRITATING TO EYES & SKIN
======================================
First Aid:REMOVE VICTIM FROM VAPORS,RESTORE BREATHING IF NECESSARY.REMOVE FROM SKIN WITH SOAP & WATER. FLUSH EYES WITH PLENTY OF WATER
======================================
Flash Point:82F-TCC Lower Limits:1.1 Upper Limits:7.0 Extinguishing Media:CARBON DIOXIDE,FOAM, OR DRY CHEMICAL Fire Fighting Procedures:DO NOT USE WATER Unusual Fire/Explosion Hazard:VAPOR MAY FORM EXPLOSIVE MIXTURE BETWEEN UPPER &LOWER EXPLOSIVE LIMITS.
=========== Accidental Release Measures ==========
Spill Release Procedures:REMOVE SOURCES OF IGNITION,APPLY SAWDUST OR OTHER ABSORBENT MATERIAL.KEEP MATERIAL FROM SPREADING
======================================
Handling and Storage Precautions:FLAMMABLE-STORE AWAY FROM OPEN FLAME AND HIGH HEAT. Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED SKIN CONTACT
====== Exposure Controls/Personal Protection =======

=== Respiratory Protection: FOR CONFINED AREAS USE BUREAU OF MINES RESPIRATORY DEVICE Ventilation: LOCAL TO KEEP BELOW LOWER EXPLOSIVE LIMIT Protective Gloves:YES Eye Protection:YES Other Protective Equipment: RUBBER SOLES. BM2304 CARTRIDGE, BM23-12 FILTERS.BM23-13 CUPS Supplemental Safety and Health ======== Physical/Chemical Properties ============ HCC:F3 Boiling Pt:B.P. Text:225-300F Vapor Density:>1.0 Evaporation Rate & Evaporation R Appearance and O dor:LIQUID Percent Volatiles by Volume:52.7 ======== Stability and Reactivity Data ========== Stability Indicator/Materials to Avoid:YES **OXIDIZERS** Hazardous Decomposition Products:CO,CO\*2,ALDEHYDES AND OTHER ORGANICS ========= Disposal Considerations ==================

Waste Disposal Methods: PUT IN METAL CONTAINER AND SEAL FOR DISPOSAL

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.