View NSN Online: https://aerobasegroup.com/nsn/8010-00-663-2673

PRATT & LAMBERT WICHITA DIV -- 704012 SEALER SANDING LACQUER TUPE -- 8010-00-663-2673

Product ID:704012 SEALER SANDING LACQUER TUPE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-663-2673

MSDS Number: BFKGB === Responsible Party ===

Company Name: PRATT & LAMBERT WICHITA DIV

Address:16116 E 13TH ST

Box:2153 City:WICHITA State:KS

ZIP:67201 Country:US CAGE:PRATT === Contract

or Identification ===

Company Name: PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY ZIP:11710 Country:US

Phone:800-647-2253

CAGE:PRATT

Company Name: PRATT AND LAMBERT INC

Address:Box:6027 City:CLEVELAND

State:OH

ZIP:44101-1027 Country:US

Phone:216-566-2902

CAGE:61196

====== Composition/Information on Ingredients ========

Ingred Name: NAPHTHA ALIPHATIC

Fraction by Wt: 25% ACGIH TLV:200PPM

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3


RTECS #:XS5250000

Fraction

by Wt: 15% OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name: ISOBUTYL ACETATE RTECS #:NP9100000 Fraction by Wt: 15% **ACGIH TLV:150PPM** Ingred Name: ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 8% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192 Ingred Name: ISOBUTYL ALCOHOL (SARA III) CAS:78-83-1 RTECS #:NP9625000 Fraction by Wt: 8% **OSHA PEL:100 PPM** ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:5000 LBS DOT Rpt Qty: 5000 LBS ========== Hazards Identification =============== Effects of Overexposure: INHAL: ANEST, IRRIT OF RESPIR TRACT OR ACMT NERV SYS DEPRESN, HDACH, DIZZ, CONFUS, UNCONSCIOUS, COMA.

First Aid:IN CASE OF CONTACT, FLUSH SKIN & EYES W/PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING. IF INHALED, REMOV TO FRESH AIR. CALLA PHYSICIAN IF SYMPTOMS PERSIST.

======== Fire Fighting Measures



GITR & EXPLOS.HAZ:WHEN EXPOSED TO EXTREME HEAT.DO NOT APPLY TO VERY HOT SURFACES.

Dhyaiaal/Ohamaiaal Dhamantiaa

======================================
HCC:F3 Boiling Pt:B.P. Text:174-246F Vapor Density:HEAV Evaporation Rate & Deference:SLOWER THAN ETHER Percent Volatiles by Volume:86
======== Stability and Reactivity Data =========
Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES.
======== Dispos

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/LOC,STAE & FEDERAL REGULATIONS.INCINERATE IN APPRVD FACILITY.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability fo

r its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.