

EASTMANK KODAK COMPANY -- 194 7738, FIXER, PROCESS C-22 -- 6750-00-680-7877

=====
Product Identification
=====

Product ID:194 7738, FIXER, PROCESS C-22

MSDS Date:01/01/1985

FSC:6750

NIIN:00-680-7877

MSDS Number: BFLHS

=== Responsible Party ===

Company Name:EASTMANK KODAK COMPANY

Emergency Phone Num:716-722-5151

CAGE:5K871

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MA

RKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

Company Name:EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address:800 LEE RD

Box:City:ROCHESTER

State:NY

ZIP:14650-3129

Country:US

Phone:800-828-6203

CAGE:5K871

=====
Composition/Information on Ingredients
=====

Ingred Name:SODIUM THIOSULFATE(CAS #7772-98-7)(95-100%)

CAS:7772-98-7

RTECS #:XN6476000

Fraction by Wt: 100%

=====

==== Hazards Identification =====

Effects of Overexposure:LOW HEALTH HAZARD

==== First Aid Measures =====

First Aid:MFR SUGGESTS NONE INDICATED,BUT GOOD INDUSTRIAL HYGIENE SHOULD BE FOLLOWED.EYES:FLUSH WITH WATER 15 MIN.SKIN:WASH WITH SOAP & WATER.GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.INHALED:REMOVE TO FRESH AI R.

==== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCES.SWEEP UP AND PLACE IN CONTAINER.FLUSH RESIDUR TO SEWER WITH COPIOUS AMOUNTS OF WATER.STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL-VENTED,LOW FIRE DISK AREA.PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED.AVOID PROLONGED OR REPEATED CONTACT.

Other Precautions:NONE

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED
Ventilation:MECHANICAL(GENERAL)
Protective Gloves:IMPERVIOUS
Eye Protection:SAFETY/CHEMICAL GOGGLES
Other Protective Equipment:NORMAL WORK CLOTHING COVERING ARMS,LEGS;SAFETY SHOES.
Supplemental Safety and Health
ITEM CONSISTS OF 5 PARTS (BLEACH, DEVELOPER, FIXER, HARDENER A & B & STOP BATH). THIS DEXCRIBES FIXER. SEE OTHER PNI THIS NSN. MSDS FOR THIS PART FM MFR DATED: 3/11/81. KEY 1: N1

==== Physical/Chemical Properties ==

=====

HCC:N1
Vapor Pres:NEG
Spec Gravity:>1
Solubility in Water:APPRECIABLE
Appearance and Odor:WHITE,ODORLESS POWDER
Percent Volatiles by Volume:NEG

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
STRONG MINERAL ACIDS
Hazardous Decomposition Products:SULFUR DOIXIDE

==== Disposal Considerations =====

Waste Disposal Methods:PLACE SOLID IN CONTAINER FOR TRANSPORT TO DISPOSAL SITE.DIS

POSE IN ACCORDANCE WITH ALL APPLICABLE
FEDERAL, STATE, AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume re
sponsibility for the suitability of this information to their
particular situation.