

CON-LUX COATINGS, INC -- GREEN 14050, ENAMEL ALKYD GLOSS, COMP L -- 8010-00-753-4549

=====  
Product Identification  
=====

Product ID:GREEN 14050, ENAMEL ALKYD GLOSS, COMP L

MSDS Date:01/01/1987

FSC:8010

NIIN:00-753-4549

MSDS Number: BFMYP

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

CAGE:6A064

=== Contr

actor Identification ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:908-287-4000

CAGE:6A064

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 49.2%

OSHA PEL:100 PPM

Ingred Name:DRIERS

Fraction by Wt: 1.3%

=====  
Hazards Identification  
=====

Effects of Overexposure:INH

:ANESTHETIC. IRRIT RESP TRACT OR ACUTE CNS  
DEPRSSN W/HDACHE,DIZ,UNCON OR COMA. SKIN & EYE:IRRIT.

=====  
First Aid Measures  
=====

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM &  
QUIET. CALL MD. SPLASH: EYES-FLUSH IMMEDIATELY W/LG AMT OF RUNNING  
WATER AT LEAST 15 MIN. SEE MD. SKIN-REMOVE W/SOAP & WATER. REMOVE  
CONTAMI NATED CLOTHING.

=====  
Fire Fighting Measures  
=====

Flash Point:105F T  
CC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO\*2, DRY CHEMICAL, OR FOAM. WATER SPRAY MAY BE  
INEFFECTIVE.

Fire Fighting Procedures:USE WATER TO COOL CL CONTAINERS. KEEP CANS  
TIGHTLY CLOSED.

Unusual Fire/Explosion Hazard:ISOLATE FROM IGNITION SOURCES. EXCESSIVE  
HEAT MAY EXPLODE CLOSED CANS. DO NOT APPLY TO HOT SURFACES.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT  
SURFACES, EL  
ECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING  
VAPORS. VENTILATE AREA. REMOVE W/INERT ABOSRBENT & NON-SPARKING  
TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP  
AWAY FROM OPEN FLAME, SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY. GROUND CONTAINERS WHEN  
POURING. AVOID PROLONGED OR REPEATED CONTACT W/SKIN. DOT:  
FLAMMABLE.

=====  
Exposure Controls/Personal Protec  
=====

tion =====

Respiratory Protection:APPROVED CHEMICAL-MECHANICAL FILTER RESP  
Ventilation:SUFFICIENT TO KEEP TLV BELOW ACCEPTABLE LIMIT  
Protective Gloves:YES  
Eye Protection:YES, FOR SPLASH  
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT  
W/CONTAMINATED CLOTHING  
Supplemental Safety and Health  
PRODUCT CONTAINS 11.7% PIGMENTS, 37.8% VEHICLE.

===== Physical/Chemical Properties =====

HCC:F4  
Boiling Pt:B.P. Text:315F  
Vapor Pres:1  
Vapor Density:4.70  
Spe  
c Gravity:0.9800  
Evaporation Rate & Reference:0.15 BUAC  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:MILD ALIPHATIC ODOR, CLEAR WATER-WHITE  
Percent Volatiles by Volume:62.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
Hazardous Decomposition Products:EMITS ACRID FUMES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IAW  
FED, ST  
ATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to

their  
particular situation.