

CON-LUX COATINGS, INC -- GREEN 14050, ENAMEL ALKYD GLOSS, COMP L -- 8010-00-753-4549

=====
Product Identification
=====

Product ID:GREEN 14050, ENAMEL ALKYD GLOSS, COMP L

MSDS Date:01/01/1987

FSC:8010

NIIN:00-753-4549

MSDS Number: BFMYP

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

CAGE:6A064

=== Contr

actor Identification ===

Company Name:CON-LUX COATINGS, INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:908-287-4000

CAGE:6A064

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 49.2%

OSHA PEL:100 PPM

Ingred Name:DRIERS

Fraction by Wt: 1.3%

=====
Hazards Identification
=====

Effects of Overexposure:INH

:ANESTHETIC. IRRIT RESP TRACT OR ACUTE CNS
DEPRSSN W/HDACHE,DIZ,UNCON OR COMA. SKIN & EYE:IRRIT.

=====
First Aid Measures
=====

First Aid:FUMES: REMOVE FROM EXPOSURE. RESTORE BREATHING. KEEP WARM &
QUIET. CALL MD. SPLASH: EYES-FLUSH IMMEDIATELY W/LG AMT OF RUNNING
WATER AT LEAST 15 MIN. SEE MD. SKIN-REMOVE W/SOAP & WATER. REMOVE
CONTAMI NATED CLOTHING.

=====
Fire Fighting Measures
=====

Flash Point:105F T
CC

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:CO*2, DRY CHEMICAL, OR FOAM. WATER SPRAY MAY BE
INEFFECTIVE.

Fire Fighting Procedures:USE WATER TO COOL CL CONTAINERS. KEEP CANS
TIGHTLY CLOSED.

Unusual Fire/Explosion Hazard:ISOLATE FROM IGNITION SOURCES. EXCESSIVE
HEAT MAY EXPLODE CLOSED CANS. DO NOT APPLY TO HOT SURFACES.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, EL
ECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE W/INERT ABOSRBENT & NON-SPARKING
TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPS. KEEP
AWAY FROM OPEN FLAME, SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY. GROUND CONTAINERS WHEN
POURING. AVOID PROLONGED OR REPEATED CONTACT W/SKIN. DOT:
FLAMMABLE.

=====
Exposure Controls/Personal Protec
=====

tion =====

Respiratory Protection:APPROVED CHEMICAL-MECHANICAL FILTER RESP
Ventilation:SUFFICIENT TO KEEP TLV BELOW ACCEPTABLE LIMIT
Protective Gloves:YES
Eye Protection:YES, FOR SPLASH
Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT
W/CONTAMINATED CLOTHING
Supplemental Safety and Health
PRODUCT CONTAINS 11.7% PIGMENTS, 37.8% VEHICLE.

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:315F
Vapor Pres:1
Vapor Density:4.70
Spe
c Gravity:0.9800
Evaporation Rate & Reference:0.15 BUAC
Solubility in Water:NEGLIGIBLE
Appearance and Odor:MILD ALIPHATIC ODOR, CLEAR WATER-WHITE
Percent Volatiles by Volume:62.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:EMITS ACRID FUMES

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS. DISPOSE IAW
FED, ST
ATE, LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to

their
particular situation.