

GOAL CHEMICAL SEALANTS CORP. -- CG-408 CLASS A -- 8030-00-753-5008

=====
Product Identification
=====

Product ID:CG-408 CLASS A

MSDS Date:01/01/1987

FSC:8030

NIIN:00-753-5008

MSDS Number: BFNJM

=== Responsible Party ===

Company Name:GOAL CHEMICAL SEALANTS CORP.

Emergency Phone Num:(213)269-0461

CAGE:04011

=== Contractor Identification ===

Company Name:GOAL CHEMICAL SEALANTS CORP

Address:3137 E 26

TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90023-4206

Country:US

Phone:213-269-0461

CAGE:04011

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

Fraction by Wt: 31.2%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:POLYSULFIDE

Fraction by Wt: 56.2%

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 12.6%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM;

9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:THIRAM (SARA III)
CAS:137-26-8
RTECS #:JO1400000
Fraction by Wt: 0.2%
OSHA PEL:5 MG/M3
ACGIH TLV:1 MG/M3; 9192
EPA Rpt Qty:10 LBS
DOT Rpt Qty:10 LBS

Ingred Name:MANGANESE DIOXIDE (AS MANGANESE)
CAS:1313-13-9
RTECS #:OP0350000
OSHA PEL:C,5 MG/M3/1 FUME TWA
ACGIH TLV:5 MG/M3 DUST/1 FUME

=====
===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE EYE OR SKIN IRRITATION OR DIZZINESS

=====
===== First Aid Measures =====

First Aid:FLUSH AFFECTED EYE W/WATER & CONSULT MD. WASH AFTER EACH USE
W/SOAP & WATER.

=====
===== Fire Fighting Measures =====

Flash Point:170F OC
Extinguishing Media:CO*2, H*2O. ETC.
Fire Fighting Procedures:NO SPECIAL PROCEDURES
Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARDS

=====
===== Accidental Release Measures =====

Spill Release Procedures:GENERAL CLEAN-UP, SCRAPE UP EX
CESS MATERIAL,
CLEAN RESIDUE W/SOLVENT

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE BELOW 80F.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:RECOMMENDED-SOLVENT VAPORS. USE NIOSH/MSHA
APPRVD RESP DEVICE
Ventilation:MFR RECM LOCAL EXHAUST
Protective Gloves:RECOMMENDED
Eye Protection:RECOMMENDED
Other Protective Equipment:NO SPECIAL EQUIP. BESIDES ABOVE
Supplemental Safety and Hea

lth

THE DRYING TIME VARIES FROM 1/2 HR. TO 2 HRS. DEPENDING ON THE AMT OF
MNO*2 ADDED TO THE PRODUCT.

===== Physical/Chemical Properties =====

HCC:V4

Appearance and Odor:LIGHT TO DARK GRAY WHEN MIXED; MERCAPTAN

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:TEMP. ABOVE 300F

Hazardous Decomposition Products:SULFUR COMPOUNDS, SO*2 GASES ETC.

Conditions to Avoid Polymeriz

ation:TEMP. ABOVE 300F

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM GENERAL TRASH DISPOSAL. DISPOSE IAW
FED., STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for

its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.