

FISKE BROTHERS REFINING CO. -- LUBRIPLATE 130-A -- 9150-00-754-0063

=====
Product Identification
=====

Product ID:LUBRIPLATE 130-A

MSDS Date:01/01/1985

FSC:9150

NIIN:00-754-0063

MSDS Number: BFNLC

=== Responsible Party ===

Company Name:FISKE BROTHERS REFINING CO.

Emergency Phone Num:(201) 589-9150

CAGE:9N579

=== Contractor Identification ===

Company Name:FISKE BROS REFINING CO

Address:129 LOCKWOOD

D ST

Box:City:NEWARK

State:NJ

ZIP:07105-4720

Country:US

Phone:201-589-9150

CAGE:73219

Company Name:FISKE BROTHERS REFINING CO

Address:1500 OAKDALE AVE

Box:City:TOLEDO

State:OH

ZIP:43605

Country:US

Phone:419-691-2491

CAGE:9N579

=====
Composition/Information on Ingredients
=====

Ingred Name:CALCIUM SOAP

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:ADDITIVE

=====

===== **Hazards Identification**=====

Effects of Overexposure:SKIN: PROLONGED/REPEATED CONTACT MAY CAUSE MILD IRRITATION.

===== **First Aid Measures**=====

First Aid:SKIN CONTACT: WASH THOROUGHLY W/SOAP & WARM WATER. EYE: FLUSH W/CLEAR WATER FOR 15 MIN. OR UNTIL IRRITATION SUBSIDES. IF IRRITATION PERSISTS, CONSULT PHYSICIAN.

===== **Fire Fighting Measures**=====

Flash Point:400F COC

Lower Limits:1

.0

Upper Limits:6.0

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER FOG OR WATER SPRAY

Fire Fighting Procedures:USE AIR SUPPLY BRTH EQUIP FOR ENCL AREAS. (SEE SUPP DATA).

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE W/STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONCENTRATED OXYGEN.

===== **Accidental Release Measures**=====

Spill Release Procedures:SCAPE UP GREASE, WASH REMAINDER W/PETROLEUM SOLVENT (TAKING APPROP PRECAUTIONS W/THIS SOLVENT AS WELL). KEEP

PETROLEUM PRODUCTS OUT OF SEWERS & WATER COURES. ADVISE AUTHORITIES IF SPILLED IN SEWERS/WA TER COURSES.

===== **Handling and Storage**=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED WHEN NOT IN USE. DO NOT HANDLE OR STORE NEAR HEAT, SPARKS, FLAME OR STRONG OXIDANTS.

Other Precautions:AVOID BREATHING OIL MIST. REMOVE OIL SOAKED CLOTHING & LAUNDER BEFORE REUSE.

===== **Exposure Controls/Personal Protection**=====

Respiratory Protection:NORMALLY NOT NEEDED ACCD TO MFR
Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES & VAPORS
Protective Gloves:OIL RESISTANT
Eye Protection:GOGGLES IF NECESSARY
Other Protective Equipment:OIL RESISTANT APRON
Supplemental Safety and Health
PERCENT VOLATILE BY VOLUME: NELGIGIBLE. FIRE FIGHTING: COOL EXPOS
CONTAINERS W/WATER SUPPLY. AVOID BREATHING VAP/FUMES.

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:>750F
Vapor Pres:.
01
Vapor Density:>14
Spec Gravity:0.96
Evaporation Rate & Reference: