

GROW GROUP INC U S PAINT DIV -- MIL-P-38336 -- 8010-00-787-8856

=====  
Product Identification  
=====

Product ID:MIL-P-38336

MSDS Date:01/01/1985

FSC:8010

NIIN:00-787-8856

MSDS Number: BFPVW

=== Responsible Party ===

Company Name:GROW GROUP INC U S PAINT DIV

Address:831 S 21ST ST

City:SAINT LOUIS

State:MO

ZIP:63103-3043

Country:US

Info Phone Num:314-621-0525 / FAX 314-621-0722

Emergency Phone Num:

314-621-0525

CAGE:90608

=== Contractor Identification ===

Company Name:US PAINT CORPORATION

Address:831 SOUTH 21ST STREET

Box:City:ST LOUIS

State:MO

ZIP:63103-3092

Country:US

Phone:314-621-0525

CAGE:90608

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL ALCOHOL (ETHANOL)

CAS:64-17-5

RTECS #:KQ6300000

Fraction by Wt: 24.0%

OSHA PEL:1000 PPM

ACGIH TLV:1000 PPM; 9192

Ingred Name:2-ETHOXYETHANOL (EGEE) (SARA III)

CAS:110-80-5

RTECS #:KK8050000

Fraction by Wt

: 12.0%  
OSHA PEL:S,200 PPM  
ACGIH TLV:S, 5 PPM; 9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:EYE AND UPPER RESPIRATORY IRRITANT

=====  
First Aid Measures  
=====

First Aid:IF EXPOSED TO EXCESS VAPOR,REMOVE TO FRESH AIR AND SEEK MED.  
ATT.IF SLASHED ON SKIN OR IN EYES,FLUS W/LG AMT OF WATER & SEEK  
IMMEDIATE MED ATT.IF INGESTED, DO NOT INDUCE VOMITING BUT SEEK  
  
IMMED MEDICAL ATTN.

=====  
Fire Fighting Measures  
=====

Flash Point:45 F TCC  
Lower Limits:2.6  
Extinguishing Media:DRY CHEMICAL OR FOAM  
Unusual Fire/Explosion Hazard:DO NOT EXPOSE OR OPEN FLAME

=====  
Accidental Release Measures  
=====

Spill Release Procedures:AFFECTED AREA SHOULD BE TREATED WITH AN  
ABSORBING MATERIAL AND THEN PLACED IN A TIGHTLY CLOSED CONTAINER.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP AWAY FROM EXCESS HEAT, SPARKS,  
AND FLAME.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:CHARCOAL BASE FOR SOLVENT VAPOR & NIOSH/MSHA  
APPROVED  
Ventilation:LOCAL EXHAUST-SUFFICIENT TO KEEP AIR SUPPLY BELOW TLV  
Protective Gloves:RUBB OR POLYETH  
Eye Protection:GOGGLES  
Other Protective Equipment:HYPERSENSITIVE PERSONS SHOULD WEAR  
PROTECTIVE CREAMS  
Supplemental Safety and Health  
VAPOR DENSITY IF H

EAVIER THAN AIR.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:167 TO 279F

Vapor Pres:3.

Spec Gravity:1.01

Evaporation Rate & Reference:1.0 N-BUAC

Solubility in Water:APPRECIABLE

Appearance and Odor:OFF WHITE-ALCOHOL

Percent Volatiles by Volume:39.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS

Stability Condition to Avoid:EXCESS HEAT

Hazardous Decomposi

tion Products:NONE

===== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/LOCAL STATE & FED CODES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this do

cument should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.