

DESOTO INC -- SUPER KOROPON PRIMER, 513-003, PT A -- 8010-00-839-3924

=====  
Product Identification  
=====

Product ID: SUPER KOROPON PRIMER, 513-003, PT A

MSDS Date: 01/01/1985

FSC: 8010

NIIN: 00-839-3924

MSDS Number: BFRZL

=== Responsible Party ===

Company Name: DESOTO INC

Address: 1700 S MT PROSPECT RD

City: DES PLAINES

State: IL

ZIP: 60018-1804

Country: US

Info Phone Num: 708-391-9000 / FAX 708-624-9420

Em

Emergency Phone Num: 708-391-9000

CAGE: 62758

=== Contractor Identification ===

Company Name: DESOTO INC

Address: 1700 S MT PROSPECT RD

City: DES PLAINES

State: IL

ZIP: 60018-1804

Country: US

Phone: 708-391-9000

CAGE: 62758

=====  
Composition/Information on Ingredients  
=====

Ingred Name: 2-ETHOXYETHYL ACETATE (CELLOSOLVE ACETATE) (EGEEA)

CAS: 111-15-9

RTECS #: KK8225000

Fraction by Wt: 15%

OSHA PEL: S, 100 PPM

ACGIH TLV: S, 5 PPM; 9192

Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA

III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 25%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:STRONTIUM CHROMATE (SARA III)

CAS:7789-06-2

RTECS #:GB3240000

Fraction by Wt: 10%

OSHA PEL:0.1 PPM CRO3;CEILING

ACGIH TLV:0.0005MG CR/M3;A2;93

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT OTHERWISE REGULATED)

CAS:1302-76-7

RTECS #:BD1450000

Fraction by Wt: 20%

OSHA P

EL:15 MG/M3 TOTAL DUST

ACGIH TLV:10 MG/M3 TDUST;8990

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

Fraction by Wt: 5%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9293

=====  
===== Hazards Identification =====

Effects of Overexposure:INH:ANESTHETIC/RESP TRACT IRRIT/CNS DEPRESS  
W/HDCH/DIZZ/UNCONS/COMA. SKIN/EYE:PRIMARY IRRIT.

=====  
===== First Aid Measures =====

First Aid:INH:MOVE FROM EXPOS/RESTORE BREATH/KE

EP WARM/QUIET. SKIN:WASH

W/H\*20/REMOVE CONTAM CLTHNG. EYES:FLUSH W/H\*20 15 MINS. ING/ALL THE ABOVE:CALL MD. REPRO/BLOOD DISORDERS/BIRTH DEFECTS OBS IN ANIMALS W/2- ETHOXYETHYL ACETATE:OBS PRECAUTIONS/AVOID OVEREXPOS.

=====  
Fire Fighting Measures  
=====

Flash Point:35F,1.7C CC

Lower Limits:1.8

Extinguishing Media:USE NFPA CLASS B EXTINGUISHERS:CO\*2, DRY CHEMICAL OR FOAM.

Fire Fighting Procedures:H\*2O SPRAY POSS INEFFECT-USE FOG NOZZLE. COOL CNTNR

S W/H\*2O.

Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY EXPLD IF EXPSD TO EXTREME HEAT. DO NOT APPLY TO HOT SURFACES. ISOLATE, CLOSE TIGHTLY

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F,49C. STORE LRG

AMTS IN BLDGS DESIGNED FOR FLAM LIQ STORAGE. GROUND CNTNRS WHEN POURING. AVOID FREE FALL OF LIQ > A FEW INCHES.

Other Precautions:DO NOT TAKE INTERNALLY. DO NOT SAND/FLAME CUT/BRAZE/WELD THE DRY COATING W/O NIOSH APPRVD RESP OR APPROPRIATE VENT. WASH CONTAMINATED CLTHNG BEFORE REUSE. OBSERVE PRECAUTIONARY LABEL WARNINGS.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH/MSHA APPRVD RESP FOR EXPOSURE OF CONCERN.

SCBA DURING FIRE

Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO KEEP TLV BELOW LIMITS.

Protective Gloves:BUTYL RUBBER

Eye Protection:SPLSH-PROOF GOG/FACE SHLD

Other Protective Equipment:PROT CLTHNG SUCH AS BUTYL RUBBER APRON. SFTY SHOWER/EYE BATH

Supplemental Safety and Health

ADDTNL INGRED:EPOXY RESIN, 25%. BP:80-156C. VAP PRESS:2.0 FOR 2-ETHOXYETHYL ACETATE TO 70 FOR MEK. THIS IS PART A OF A TWO PART KIT.

=====  
Physical/Chemical Properties  
=====

HCC

:F2

Boiling Pt:B.P. Text:176-313F

Vapor Density:>1.0

Evaporation Rate & Reference: