

DIGITAL EQUIPMENT CORP-DIST (DOW CORNING CORP-MFR) -- LPS4X-AC (DOW CORNING 200 FLUID,350 CST) -- 9150-00-851-4257

=====
===== Product Identification =====

Product ID:LPS4X-AC (DOW CORNING 200 FLUID,350 CST)

MSDS Date:04/09/1986

FSC:9150

NIIN:00-851-4257

MSDS Number: BFSQZ

=== Responsible Party ===

Company Name:DIGITAL EQUIPMENT CORP-DIST (DOW CORNING CORP-MFR)

Address:146 MAIN STREET

City:MAYNARD

Stat

e:MA

ZIP:01754-5111

Emergency Phone Num:617-646-0220

CAGE:15476

=== Contractor Identification ===

Company Name:COMPAQ/ FORMERLY KNOWN AS-DIGITAL EQUIPMENT CORP

Address:111 POWDERMILL RD

Box:City:MAYNARD

State:MA

ZIP:01754-2504

Country:US

Phone:508-479-3046

CAGE:15476

=====
===== Composition/Information on Ingredients =====

Ingred Name:DIMETHYL POLYSILOXANE (MONOMER:DIMETHYL SILOXANE)

CAS:63148-62-9

RTECS #:JT6484500

Fraction by Wt: 100%

Other REC Limits:N/K

OSHA PEL:N/K

ACGIH TLV

:N/K

=====
===== Hazards Identification =====

LD50 LC50 Mixture:N/K

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:NO ADVERSE TOXIC EFFECTS OF A CHRONIC NATURE ARE KNOWN BY MANUFACTURER.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:MAY CAUSE TEMPORARY EYE

DISCOMFORT.INHAL:UNNECESSARY EXPOSURE TO THIS OR ANY OTHER CHEMICAL SHOULD BE AVOIDED.SKIN:SINGLE PROLONGED EXP TO SKIN PRODUCES NO KNOWN ADVE

RSE EFFECT & NO INJURY IS LIKELY FROM RELATIVELY BRIEF
INHALATION EXP. SMALL AMTS TRANSFERRED TO MOUTH DURING NORMAL WORK
SHOULD NOT CAUSE INJURY.

Medical Cond Aggravated by Exposure:N/K

===== First Aid Measures =====

First Aid:EYES-FLUSH WITH WATER FOR AT LEAST 15 MINUTES OCCASIONALLY
LIFTING UPPER & LOWER LIDS.IF IRRIT PERSISTS,GET MED ATTN.SKIN-WASH
WITH SOAP & WATER.IF IRRIT PERSISTS,GET MED ATTN.INH-FOR LARGE
AMOUNTS,MOVE TO FRESH
AIR.IF NEC,SUPPORT BREATHING.KEEP WARM & AT
REST.GET MED ATTN.INFORM MD OF INFORMATION IN MSDS.INGEST-GET MED
ATTN.INFORM MD OF INFORMATION IN MSDS.

===== Fire Fighting Measures =====

Flash Point Method:OC
Flash Point:600F,315C
Lower Limits:N/K
Upper Limits:N/K
Extinguishing Media:WATER,FOAM,DRY CHEMICAL.
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA AND FULL
PROTECTIVE EQUIPMENT .
Unusual Fire/Explosion Hazard:SILICON DIOXIDE,CARBON DIOXIDE,
AND TRACES
OF INCOMPLETELY BURNED CARBON PRODUCTS ARE DECOMPOSITION PRODUCTS.

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBANT MATERIAL TO COLLECT AND CONTAIN
FOR SALVAGE.
Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:KEEP CONTAINER CLOSED.AVOID ELEVATED
TEMPERATURES.
Other Precautions:GOOD PRACTICE REQUIRES THAT GROSS AMOUNT OF ANY
CH

EMICAL SHOULD BE REMOVE FROM SKIN AS SOON AS PRACTICAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE OF CONCERN .

Ventilation:EACH SITUATION MUST BE EVALUATED BASED UPON EXPOSURES OF CONCERN .

Protective Gloves:NOT NEEDED FOR NORMAL USE.

Eye Protection:CHEMICAL WORKERS GOGGLES .

Other Protective Equipment:NOT NEEDED FOR NORMAL USE.

Work Hygienic Practices:N/K

Supplemental Safety and Health

PHYSICAL DATA-VAPOR PRESSURE,5 MMHG AT 77F,25C.SPECIFIC GRAVITY,0.98 AT 77F,25C.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:>300F,149C

Decomp Temp:Decomp Text:N/K

Vapor Pres:SUPP DATA

Spec Gravity:SUPP DATA

Evaporation Rate & Reference: