

N & M PAINT MFG. CO. -- TT-E-489F RED ENAMEL -- 8010-00-889-7345

=====  
Product Identification  
=====

Product ID:TT-E-489F RED ENAMEL

MSDS Date:01/01/1987

FSC:8010

NIIN:00-889-7345

MSDS Number: BFTYD

=== Responsible Party ===

Company Name:N & M PAINT MFG. CO.

Emergency Phone Num:401-726-3650

CAGE:MO162

=== Contractor Identification ===

Company Name:FEDERAL SPECIFICATIONS, PROMULGATED BY GSA

Box:Cit

y:WASHINGTON

State:DC

Country:US

CAGE:81348

Company Name:N & M PAINT MFG. CO.

CAGE:MO162

=====  
Composition/Information on Ingredients  
=====

Ingred Name:TOLUIDINE RED

RTECS #:XU8375200

Fraction by Wt: 9%

Ingred Name:ALKYD RESIN

Fraction by Wt: 37%

Ingred Name:MINERAL SPIRITS -RULE 66

Fraction by Wt: 54%

=====  
Fire Fighting Measures  
=====

Flash Point:107F TCC 41C

Extinguishing Media:FOAM

Fire Fighting Procedures:USE ONLY FOAM

=====

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP W/PAINT THINNER

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE.

===== Exposure Controls/Personal Protection =====

Ventilation:MECH-USE EXHAUST FAN

Protective Gloves:NO

Eye Protection:NO

Other Protective Equipment:WEAR MASK WHEN SPRAYING

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:318F

Spec Gravity:0.769

Evaporation Rate & Reference:TOLUENE 0.06

Solubility in Water:NO

Percent Volatiles by Volume:100

===== Disposal Considerations =====

Waste Disposal Methods:LAND FILL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.